

FJAF-A074-CAA-140

HFC, R-404A, 60Hz, 1- Phase, 115 V

**Availability : Obsolete****Mechanical**

Unit Height (in):	12.0
Unit Length (in):	17.5
Unit Width (in):	14.3
Ship Weight (lbs):	73.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 F
Suction Connection Size (in)/Type:	5/8 F
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	24

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	20.7
Compressor:	RS64C1E-CAA-106
Compressor LRA - Low:	
Compressor LRA - High:	59.0
Compressor LRA - Half winding:	
Compressor RLA:	15.2
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	1.4
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	02-Oct-2002	Return Gas Temp. (°F):	40	
Compressor:	RS64C1E-CAA-106 x 1	Subcooling (°F):	5	
Performance No:	5718	Air Flow Rate (CFM)	450	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-25	2,100	104.3	14.3	2.1
-20	2,540	106.1	16.1	2.4
-15	2,990	108.1	18.1	2.7
-10	3,460	110.0	20.0	2.9
-5	3,930	111.9	21.9	3.1
0	4,390	114.3	24.3	3.3
5	4,910	116.0	26.0	3.6
10	5,400	118.3	28.3	3.7
15	5,910	120.4	30.4	3.9
20	6,420	122.6	32.6	4.0
25	6,940	124.9	34.9	4.1