



- Waterproof- Forms a Tight, Strong Seal
- Versatile- Use on Dry or Damp Surfaces
- Dries Black

WHAT IS ALL-WEATHER CEMENT & WHERE DO I USE IT? Black Jack® 2172 All-Weather Roof Cement is a black asphalt product ideal for sealing, filling and patching cracks and breaks in roofing surfaces, firewalls, chimneys, gutters, flashing, etc., particularly where emergency repairs of wet surfaces must be done. Use this product to repair shingle tabs, flashings, roof seams and gable joints. It can also be used to stop leaks around vent pipes and is suitable for sealing metal building seams, foundations, masonry steps and for repointing chimneys. Black Jack Roof Cement cannot be painted.

HOW DO I PREPARE THE SURFACE? Remove dust, dirt and debris using stiff brush or broom. Remove crusted rust or sealed previous coating by scraping or wire brushing.

WHAT IS THE COVERAGE? Each 10.1 ounce cartridge covers approximately 30 linear feet of 1/4" x 1/4" bead.

HOW DO I CLEAN-UP? Tools should be cleaned with paint thinner or mineral spirits.

HOW DO I APPLY IT AND WHAT THICKNESS? Cut spout to desired bead size and puncture inner seal. Using a standard caulking gun apply directly over area to be sealed. Black Jack Roof Cement may be tooled with a trowel or putty knife, occasionally dipped in paint thinner. Emergency repairs should be considered temporary and should be reapplied with thorough surface preparation when weather conditions improve. When application is to take place at temperatures below 50°F (10°C), store Black Jack Roof Cement at room temperature 24 hours prior to use in order to make gunning easier. Surfaces may be wet at time of application, but must be free of frost, snow and ice.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Flash Point	105°F (41°C)
Weight Per Gallon, lbs.	10.0 lbs.
Consistency	Trowel
Residue by evaporation, %	70% min.
Combustible Solvents	Mineral Spirits
Cure Time (at recommended coverage rate)	4-8 hours to set, 24-48 hrs. to cure depending on surface and weather.
Application Temperature	50°-120°F

Approx. Shipping Weights: (Note: All approx. weights include container.)

10 fl oz (300mL)	0.7 lb.
29 fl oz	3 lbs.

**CAUTION: COMBUSTIBLE. HARMFUL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.**

CAUTION: For exterior use only. Contains petroleum based products. Keep away from heat, sparks, and open flame. Use only with adequate ventilation. Eye and skin irritant. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid contact with skin and breathing vapor. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. Do not use in drinking water or food systems. Avoid prolonged breathing of vapor or spray mist. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

VOC = 250 g/l (2.1 lb/gal) Maximum

Asphalt	CAS# 8052-42-4
Mineral Spirits	CAS# 8052-41-3
Calcium Carbonate	CAS# 471-34-1
Clay	CAS# 1332-58-7
Cellulose	CAS# 65996-61-4
Quartz	CAS# 13808-60-7

Product is Asbestos Free.
PATENT PENDING

©2007 Gardner-Gibson, Inc. Manufactured by/Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449
Tampa, FL 33675
www.gardner-gibson.com

See MSDS for more info

LIMITED WARRANTY: The Gardner-Gibson Company warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, is free of defects in material and workmanship for a period of one (1) year from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.gardner-gibson.com