

FJAL-A225-TFC-020

HFC, R-404A, 60Hz, 3- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	18.9
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	188.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	45

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.1
Compressor:	CF06K6E-TF5-295
Compressor LRA - Low:	
Compressor LRA - High:	52.0
Compressor LRA - Half winding:	
Compressor RLA:	7.0
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	28-May-2002	Return Gas Temp. (°F):	40
Compressor:	CF06K6E-TF5-295 x 1	Subcooling (°F):	5
Performance No:	3699	Air Flow Rate (CFM)	1680

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-30	4,350	100.1	10.1	3.0
-25	5,380	101.3	11.3	3.4
-20	6,510	102.6	12.6	3.8
-15	7,730	104.1	14.1	4.1
-10	9,010	105.6	15.6	4.4
-5	10,300	107.3	17.3	4.7
0	11,600	109.2	19.2	5.0