

## 5" Diameter Single Shaft Open Fan/Blower Motors

### Furnace Blowers - Attic Ventilators - Air Handlers - Fan Coils

#### Features:

- Continuous Duty, Air Over • Shaded Pole • 60 Hz • Auto Protector • 40°C Ambient
- 1/2" Flatted Shaft


OEM replacement for: Intertherm, Triangle Engineering, Butler Ventimatic, Tuttle & Bailey, Leigh Products, Nutone, Kool-O-Matic, Luxaire, Duotherm, Lennox, Coleman, Lear Siegler, Bryant, Janitrol, Westinghouse, American Standard, Miller, Johnson, Preway, etc.



| HP                | RPM  | Speeds | Volts   | Amps            | Stock Number | Bearings | Rotation | Dim. Ref. | Notes    |
|-------------------|------|--------|---------|-----------------|--------------|----------|----------|-----------|----------|
| 1/5               | 1050 | 1      | 115     | 6.7             | 9690         | Sleeve   | CCWLE    | 9         | 7,26     |
| 1/5               | 1050 | 1      | 115     | 6.0             | BL6413       | Sleeve   | CCWLE    | 6         | 7,22,26  |
| 1/5~1/8           | 1050 | 2      | 115     | 6.8-4.2         | 684          | Sleeve   | CCWLE    | 2         | 7,26,123 |
| 1/5~1/6~1/8       | 1050 | 3      | 115     | 6.8-5.3-4.2     | 385          | Sleeve   | CCWLE    | 3         | 7,26     |
| 1/5~1/6~1/8       | 1050 | 3      | 115     | 6.8-5.3-4.2     | 9695         | Sleeve   | CCWLE    | 10        | 7,26     |
| 1/5~1/6~1/8       | 1075 | 3      | 115     | 6.4-4.8-3.7     | 9403         | Sleeve   | CCWLE    | 5         | 3,7      |
| 1/5~1/8~1/10      | 1050 | 3      | 115     | 6.5-4.0-3.0     | BL6414       | Sleeve   | CCWLE    | 7         | 7,22,26  |
| 1/5~1/7~1/9~1/12  | 1050 | 4      | 115     | 7.9-5.8-4.3-3.5 | 559          | Sleeve   | CCWLE    | 4         | 7,26     |
| 1/5~1/8~1/10~1/15 | 1050 | 4      | 115     | 7.1             | BL6416       | Sleeve   | CCWLE    | 8         | 7,22,26  |
| 1/5~1/8~1/10      | 1050 | 3      | 208-230 | 3.2-2.1-1.5     | B6415        | Sleeve   | CCWLE    | 7         | 7,22,26  |
| 1/5~1/6~1/8       | 1050 | 3      | 208-230 | 3.4-2.7-2.2     | 429          | Sleeve   | CCWLE    | 3         | 7,26     |
| 1/5~1/6~1/8       | 1050 | 3      | 208-230 | 3.4-2.7-2.2     | 9696         | Sleeve   | CCWLE    | 10        | 7,26     |
| 1/4               | 1050 | 1      | 115     | 8.9             | BL6531       | Sleeve   | CCWLE    | 11        |          |
| 1/4               | 1050 | 1      | 115     | 9.4             | BLR640S      | Sleeve   | CCWLE    | 12        | 7,26,357 |
| 1/4               | 1050 | 1      | 115     | 12.3            | BLR6401      | Sleeve   | CCWLE    | 13        | 7,26     |
| 1/4~1/6~1/8       | 1050 | 3      | 115     | 8.2-4.3-3.4     | BL6534       | Sleeve   | CCWLE    | 11        |          |
| 1/4~1/6~1/8       | 1050 | 3      | 115     | 8.2-4.2-3.4     | BLR6404      | Sleeve   | CCWLE    | 12        | 7,26,357 |

#### Notes:

3. Special OEM Replacement Motor (see pages 94-132)
7. Resilient Mounting Rings Included
22. 3 Thru Bolts, 4.42" dia. Bolt Circle
26. Extended thru bolts, shaft end only
123. Stock 684 "BM" dimension was 4", motors built after 4/98 will have an "BM" dimension of 3-3/4")
357. 4 thru bolts, 4.42" dia. bolt circle



#### Approximate Dimensions

| Ref. | BM   | C     | N    | R    |
|------|------|-------|------|------|
| 1    | 4.00 | 7.75  | 3.75 |      |
| 2    | 3.75 | 7.59  | 3.84 | 4.22 |
| 3    | 4.00 | 7.84  | 3.84 | 4.56 |
| 4    | 4.00 | 8.08  | 4.08 | 4.56 |
| 5    | 4.00 | 6.97  | 2.97 | 4.56 |
| 6    | 3.34 | 8.88  | 5.54 | 4.08 |
| 7    | 3.84 | 9.38  | 5.54 | 4.58 |
| 8    | 3.84 | 6.50  | 2.66 | 4.58 |
| 9    | 4.00 | 7.75  | 3.75 | 4.56 |
| 10   | 5.00 | 10.50 | 5.50 | 5.56 |
| 11   | 4.09 | 8.59  | 4.50 |      |
| 12   | 4.34 | 8.84  | 4.50 | 5.08 |
| 13   | 5.00 | 8.13  | 3.13 | 5.56 |