

ZB11KCE-PFV

HFC, R-404A, 50Hz, 1- Phase, null V
Medium Temperature



Production Status: Preliminary data only - Contact your Emerson Climate Technologies Representative.

Performance

<u>Evap(°F)/Cond(°F)</u>		
Capacity (Btu/hr) Power (Watts):		
Current (Amps):		
EER (Btu/Wh):		
Mass Flow (lbs/hr):		
Sound Power (dBA):	67 Avg	72 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-07-09	

Mechanical

Number of Cylinders:	Displ(in ³ /Rev):
Bore Size(in):	Displ(ft ³ /hr):
Stroke(in):	
Overall Length (in):	Mounting Length (in):
Overall Width (in):	Mounting Width (in):
Overall Height (in):	Mounting Height (in): *
Suction Size (in):	null
Discharge Size (in):	null
Oil Recharge (oz):	
Initial Oil Charge (oz):	
Net Weight (lbs):	
Internal Free Volume (in ³):	120.0
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*:	MCC (Amps):	UL File No:
LRA-Half Winding:	RPM:	2900 UL File Date:
LRA Low*:	Max Operating Current:	null
RLA(=MCC/1.4;use for contactor selection):	1	
RLA(=MCC/1.56;use for breaker & wire size selection):	null	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.		

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
--------------------	------------------	--------------	----------------	--------------------