

M4FL-0067-CFA-272

HFC, R-404A, 60Hz, 1- Phase, 115 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	11.8
Unit Length (in):	18.1
Unit Width (in):	14.4
Ship Weight (lbs):	70.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	1/2 S
Discharge Line Size(in):	0.250
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	21

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	12.7
Compressor:	AFT26C1E-CFA-103
Compressor LRA - Low:	
Compressor LRA - High:	72.0
Compressor LRA - Half winding:	
Compressor RLA:	8.8
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	1.4
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	06-Apr-2005	Return Gas Temp. (°F):	40	
Compressor:	AFT26C1E-CFA-103 x 1	Subcooling (°F):	5	
Performance No:	7707	Air Flow Rate (CFM)	450	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-25	2,190	103.6	13.6	2.7
-20	2,520	105.0	15.0	2.9
-15	2,890	106.6	16.6	3.1
-10	3,290	108.4	18.4	3.3
-5	3,740	110.2	20.2	3.5
0	4,200	112.7	22.7	3.7