

Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	19.1
Unit Length (in):	33.4
Unit Width (in):	20.0
Ship Weight (lbs):	207.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	22

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	14.2
Compressor:	KALB-015E-CAV-100
Compressor LRA - Low:	
Compressor LRA - High:	55.0
Compressor LRA - Half winding:	
Compressor RLA:	9.9
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	1.5
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	25-Jul-2002	Return Gas Temp. (°F):	65
Compressor:	KALB-015E-CAV-100 x 1	Subcooling (°F):	5
Performance No:	4128	Air Flow Rate (CFM)	1510

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	3,690	100.9	10.9	2.6
-35	4,390	102.0	12.0	2.9
-30	5,140	103.2	13.2	3.2
-25	5,960	104.4	14.4	3.4
-20	6,830	105.8	15.8	3.7
-15	7,760	107.3	17.3	4.0
-10	8,750	108.9	18.9	4.3
-5	9,810	110.5	20.5	4.5
0	10,900	112.6	22.6	4.8