

DJAL-0075-CAA-212

HFC, R-404A, 60Hz, 1- Phase, 115 V



Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	11.4
Unit Length (in):	19.8
Unit Width (in):	22.5
Ship Weight (lbs):	141.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	5/8 F
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	22

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	15.4
Compressor:	KAMB-007E-CAA-100
Compressor LRA - Low:	
Compressor LRA - High:	85.5
Compressor LRA - Half winding:	
Compressor RLA:	10.9
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.58
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	23-Sep-2002	Return Gas Temp. (°F):	65
Compressor:	KAMB-007E-CAA-100 x 1	Subcooling (°F):	5
Performance No:	5644	Air Flow Rate (CFM)	650

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	1,900	102.3	12.3	2.8
-30	2,470	104.6	14.6	3.2
-20	3,330	107.9	17.9	3.8
-10	4,370	112.0	22.0	4.3
0	5,420	116.7	26.7	4.7
-35	2,140	103.3	13.3	3.0
-25	2,870	106.1	16.1	3.5
-15	3,840	109.9	19.9	4.0
-5	4,910	114.1	24.1	4.5