

C8AL-0151-TAC-001

HCFC, R-22, 60Hz, 3- Phase, 208/230 V



Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	19.1
Unit Length (in):	33.4
Unit Width (in):	20.0
Ship Weight (lbs):	282.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 F
Suction Connection Size (in)/Type:	7/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	60

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	10.3
Compressor:	EADA-020E-TAC-100
Compressor LRA - Low:	
Compressor LRA - High:	46.0
Compressor LRA - Half winding:	
Compressor RLA:	6.8
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	1.5
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	04-Oct-2002	Return Gas Temp. (°F):	65
Compressor:	EADA-020E-TAC-100 x 1	Subcooling (°F):	5
Performance No:	5813	Air Flow Rate (CFM)	1510

90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	3,410	98.4	8.4	2.8
-35	4,180	100.0	10.0	3.1
-30	5,020	101.7	11.7	3.4
-25	5,930	103.5	13.5	3.7
-20	6,910	105.5	15.5	4.0
-15	7,960	107.6	17.6	4.3
-10	9,100	109.8	19.8	4.6
-5	10,300	112.1	22.1	4.9
0	11,600	114.7	24.7	5.1