

ZPD182KCE-TW5

HFC, R-410A, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	183000	223000
Power (Watts):	16700	12500
Current (Amps):	53.40	44.10
EER (Btu/Wh):	11.00	17.80
Mass Flow (lbs/hr):	2690	2750
Sound Power (dBA):	82 Avg	87 Max
Vibration (mils(peak-peak)):	3.0 Avg	4.5 Max
Record Date:	2009-03-04	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	10.20
Bore Size(in):	0.00	Displ(ft ³ /hr):	1239.34
Stroke(in):	0.00		
Overall Length (in):	12.83	Mounting Length (in):	7.50
Overall Width (in):	11.61	Mounting Width (in):	7.50
Overall Height (in):	21.71	Mounting Height (in):	22.46 *
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	110		
Net Weight (lbs):	147		
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	340.0	MCC (Amps):	87.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	07-Feb-2007
LRA Low*:		Max Operating Current:	74.0		
RLA(=MCC/1.4;use for contactor selection):	62.1				
RLA(=MCC/1.56;use for breaker & wire size selection):	55.8				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-410A HFC	50	3	200/220	A/C, 50% Load Of Compressor
R-410A HFC	60	3	200/230	A/C, 50% Load Of Compressor
R-410A HFC	50	3	200/220	Air Conditioning