

DJAL-026Z-CFV-020

HFC, R-404A, 60Hz, 1- Phase, 208/230 V



Availability : **Obsolete**

Mechanical

Unit Height (in):	19.0
Unit Length (in):	25.2
Unit Width (in):	34.0
Ship Weight (lbs):	0.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1-1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	47

Electrical

Max Fuse Size:	45
Min Circuit Ampacity:	28.7
Compressor:	ZF11K4E-PFV-231
Compressor LRA - Low:	
Compressor LRA - High:	109.0
Compressor LRA - Half winding:	
Compressor RLA:	20.7
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	2.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	06-Sep-2007	Return Gas Temp. (°F):	65
Compressor:	ZF11K4E-PFV-231 x 1	Subcooling (°F):	5
Performance No:	7808	Air Flow Rate (CFM)	2170

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-35	9,580	102.6	12.6	3.4
-30	10,800	103.6	13.6	3.7
-25	12,200	104.6	14.6	4.0
-20	13,600	105.8	15.8	4.3
-15	15,200	107.0	17.0	4.7
-10	16,800	108.4	18.4	5.0
-5	18,600	109.7	19.7	5.3
0	20,400	111.7	21.7	5.6
-40	8,420	101.8	11.8	3.0