

M4CL-0075-CAV-212

HFC, R-404A, 60Hz, 1- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	11.7
Unit Length (in):	23.5
Unit Width (in):	13.3
Ship Weight (lbs):	78.0
Condensor Type:	
CopeVap Water Storage:	
Liquid Connection Size (in)/Type:	1/4 S
Suction Connection Size (in)/Type:	5/8 S
Discharge Line Size(in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	15

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	12.3
Compressor:	RST64C1E-CAV-108
Compressor LRA - Low:	
Compressor LRA - High:	43.0
Compressor LRA - Half winding:	
Compressor RLA:	9.0
UL:	Recognized
UL File #:	SA633
UL Guide Card:	LZFE2
Amps Per Motor:	0.7
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	04-Nov-2010	Return Gas Temp. (°F):	40
Compressor:	RST64C1E-CAV-108 x 1	Subcooling (°F):	5
Performance No:	8102	Air Flow Rate (CFM)	400

90°F Ambient Air Temperature

<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-25	2,520	106.6	16.6	3.0
-20	2,930	108.5	18.5	3.3
-15	3,360	110.5	20.5	3.5
-10	3,790	112.6	22.6	3.7
-5	4,230	114.7	24.7	3.8
0	4,650	117.2	27.2	4.0