

DJAL-015Z-CFV-081

HFC, R-404A, 60Hz, 1- Phase, 208/230 V



Availability : **Standard US Wholesaler**

Mechanical

Unit Height (in):	18.9
Unit Length (in):	25.0
Unit Width (in):	34.0
Ship Weight (lbs):	205.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	3/8 S
Suction Connection Size (in)/Type:	1 1/8 S
Discharge Line Size(in):	0.500
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	46

Electrical

Max Fuse Size:	30
Min Circuit Ampacity:	19.3
Compressor:	ZF06K4E-PFV-231
Compressor LRA - Low:	
Compressor LRA - High:	61.0
Compressor LRA - Half winding:	
Compressor RLA:	13.6
UL:	
UL File #:	
UL Guide Card:	
Amps Per Motor:	0.6
Fan Motor Quantity:	2

Air - Cooled Unit Performance

Release Date:	13-Jan-2006	Return Gas Temp. (°F):	65	
Compressor:	ZF06K4E-PFV-231 x 1	Subcooling (°F):	5	
Performance No:	7779	Air Flow Rate (CFM)	1680	
90°F Ambient Air Temperature				
<u>Evap Temp</u> <u>(°F)</u>	<u>Unit Capacity</u> <u>(Btu/hr)</u>	<u>Cond. Temp.</u> <u>(°F)</u>	<u>Temp. Diff.</u> <u>(°F)</u>	<u>EER</u> <u>(Btu/Wh):</u>
-40	4,750	100.8	10.8	2.6
-35	5,460	101.6	11.6	2.9
-30	6,220	102.4	12.4	3.3
-25	7,020	103.3	13.3	3.6
-20	7,870	104.3	14.3	3.9
-15	8,770	105.4	15.4	4.2
-10	9,730	106.5	16.5	4.5
-5	10,700	107.7	17.7	4.8
0	11,800	109.4	19.4	5.0