



## Looking for more information?

Visit us on the web at <http://www.artisan-scientific.com> for more information:

- Price Quotations
- Drivers
- Technical Specifications, Manuals and Documentation

## Artisan Scientific is Your Source for Quality New and Certified-Used/Pre-owned Equipment

- Tens of Thousands of In-Stock Items
- Hundreds of Manufacturers Supported
- Fast Shipping and Delivery
- Leasing / Monthly Rentals
- Equipment Demos
- Consignment

### Service Center Repairs

Experienced Engineers and Technicians on staff in our State-of-the-art Full-Service In-House Service Center Facility

### InstaView™ Remote Inspection

Remotely inspect equipment before purchasing with our Innovative InstaView™ website at <http://www.instraview.com>

### We buy used equipment! We also offer credit for Buy-Backs and Trade-Ins

Sell your excess, underutilized, and idle used equipment. Contact one of our Customer Service Representatives today!

Talk to a live person: 888-88-SOURCE (888-887-6872) | Contact us by email: [sales@artisan-scientific.com](mailto:sales@artisan-scientific.com) | Visit our website: <http://www.artisan-scientific.com>

Availability :OEM and Wholesaler Standard

**Mechanical**

Unit Height (in):	31.5
Unit Length (in):	44.1
Unit Width (in):	36.0
Ship Weight (lbs):	684.0
Condenser Type:	Air
Copevap Water Storage:	NA
Receiver Capacity (lbs):	55.4
Liquid Connection Size (in)/Type:	5/8 F
Suction Connection Size (in)/Type:	1-3/8 S
Discharge Line Size(in):	1 1/8
Water Inlet ( ):	
Water Outlet ( ):	
Oil Type:	POE
Oil Recharge Amount (oz):	125

**Electrical**

Max Fuse Size:	60
Min Circuit Ampacity:	42.3
Compressor:	3DA3F28KE-TFC-100
Compressor LRA - Low:	
Compressor LRA - High:	150.0
Compressor LRA - Half winding:	
Compressor RLA:	30.3
UL:	None
UL File #:	None
UL Guide Card:	None
Amps Per Motor:	4.1
Fan Motor Quantity:	1

**Air - Cooled Unit Performance**

Release Date:	20-Jul-2002	Return Gas Temp. (°F):	65
Compressor:	3DA3F28KE-TFC-100 x 1	Subcooling (°F):	5
Performance No:	3930	Air Flow Rate (CFM):	3240

90°F Ambient Air Temperature			
<u>Evap.</u> <u>Temp.</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)
-40	15,600	99.9	9.9
-35	18,100	101.0	11.0
-30	21,000	102.2	12.2
-25	24,100	103.6	13.6
-20	27,600	105.0	15.0
-15	31,300	106.7	16.7
-10	35,300	108.4	18.4
-5	39,400	110.1	20.1
0	43,500	112.2	22.2

# Condensing Unit Model Number Nomenclature

## All Models Except M-Line

Design Series and Refrigerant	
Letters (Except K,L,M)	R-12
K, L	R-22 LT
M	R-22 LT Discus
Numbers (Except 6 & 7)	R-22/R-502
6, 7	R-12/R-502
X, 9	Special Designs
(Different series type may indicate a major design revision.)	

New HFC Refrigerant Indicator		
Pressure Rating	Standard	Special
<u>Approved Refrigerants</u>	<u>Models</u>	<u>Designs</u>
Medium	T	R
High and Medium	P	N
High	J	E

Compressor Motor Type	
Single Phase Motors	
Capacitor Run-Capacitor Start	C
Induction Run-Capacitor Start	I
Induction Run-Split Phase	S
Induction Run-Capacitor Start, Low Torque	X
Capacitor Run-Permanent Split Capacitor	P
Three Phase Motors	
General	T
3 Lead Single Voltage	
6 Lead Part Winding 575 V	
9 Lead Dual Voltage	
Star (Wye) Delta	E
6 Lead Motors	F
Part Winding or Across the Line	

Bill of Material Product Variations	
Variation (B/M)	UL/CSA Eligibility
Number	
001 thru 099	Intended for UL Listing and CSA Certified.
100 thru 299	Intended for UL Recognition and CSA Certified.
300 thru 399	Not Eligible for either UL Listing, UL Recognition, or CSA Certified.

X X X X - X X X X - X X X - X X X

### Condensing Unit Family Series

Type of Design	
Type	Code
Air Cooled	A
No condenser	N
Water Cooled	W
Evaporating	
Pan Base	E
Discus	D

Application Temperature*	
Temperature Range	Code
High Temperature	H
45°F Max.; 0°F Min.	
Medium Temperature	M
25°F Max.; -5°F Min.	
Medium Temperature	F
25°F Max.; -25°F Min.	
Low Temperature	L
0°F Max.; -40°F Min.	
Extra Low Temperature	E
-20°F Max.; -40°F Min.	
Two Stage	T
0°F Max.; -40°F Min.	
Two Stage (Extra Low)	U
-30°F Max.; -80°F Min.	
Commercial Application	C
High & Med. Temperature	
Single Refrigerant	
Dual Application	D
R-22 HT, R-502 MT	
Multiple Application	B
R-12 H/MT, R-502 LT	

\*NOTE: Limited or extended range will be shown in performance data tables.

Typical Motor Rating	
Nominal (HP)	Code
1/4	0025
1/3	0033
1/2	0050
3/4	0075
1	0100
1-1/2	0150
2	0200
2-1/2	0250
3	0300
3-1/2	0350
4	0400
5	0500
6	0600
7-1/2	0750
9	0900
10	1000
15	1500
20	2000
22	2200
25	2500
27	2700
30	3000
40	4000
50	5000
60	6000
70	7000
80	8000

NOTE: Left hand position may contain a letter indicating a revision (on units less than 10 HP).

Right hand position may contain the letter "Z" indicating a Glacier™ Scroll compressor.

Compressor Motor Protection	
Type Protection	Code
External Inherent Protection—	A
One Protector, (Line Break)	
Use with Contactor (single or three phase)	
Internal Inherent Protection—	F
One Protector, Use with Contactor. (single or three phase)	
Internal Thermostat(s); H and External Supplementary Protector(s). (Two for 3Ø, one for 1Ø.)	
Use with Contactor.	
Internal Thermostat(s); L and Three External Supplementary Protectors. Use with Contactor.	
Internal Thermal Protectors—Electronic Sensors; and Control Module External. Use with contactor.	S
Internal Thermal Protectors—Electronic sensors; and control module external. Use with contactor. (For European use only).	W

Typical Electrical Codes		
60 Hz.	50 Hz.	Code
115-1	100-1	A
230-1	200-1	B
208/230-3	200/220-3	C
460-3	380/400-3	D
575-3	500-3	E
-	115-1	F
-	230-1	G
208-1	200-1	H
-	208/230-1	I
265-1	220/240-1	J
208/230/460-3	200/400-3	K
-	210/240/380-3	L
-	380/420-3	M
230/460-3	200/400-3	N
All D.C. Ratings		O
-	200/380-3	P
-	200/240-3	R
-	220-1	S
-	200-1	T
200-3	-	U
208/230-1	200-1	V
-	200/220-3	W
Misc. A.C. Ratings		X
-	500-3	Y
-	220/240-1	Z
200-1	200-1	3
100-1	100-1	4
200/230-3	-	5
230-3	-	6

NOTE: When applicable, specific 50 Hz ratings (not necessarily identical to typical shown above) will be shown as alternate on 60 Hz rated models.



# CJDL-0601-TFC-001

HFC , R-404A ,50 Hz, 3 - Phase , 200/220 V

Availability :OEM and Wholesaler Standard




## Features

Includes dual pressure control, oil pressure safety control and contactor, all mounted and wired

Includes line voltage fan motor mounted and wired

U.L. Listed and C.S.A. Certified

**Service Parts**

<u>Reference</u>	<u>Part Number</u>	<u>Quantity</u>	<u>Description</u>
43	024-0195-00	1	GUARD-FAN
10	036-0010-00	1	FITTING-UNION
10	036-0013-02	1	FITTING-UNION
26	050-0248-00	1	MOTOR-FAN
17	066-0262-00	1	CONDENSER-AIR
13	071-0429-08	1	PROTECTOR
12	074-0645-01	1	BRACKET-FAN MOTOR MTG
42	074-7006-00	1	BRACKET-CONTROL MTG
22	083-0115-01	1	BLADE-FAN
1	3DA3A060E-TFC-800	1	COPE COMP
2	3DA3F28KE-TFC-800	1	COPE COMP
9	505-0193-00	1	COVER-ASSEMBLY
44	545-0021-00	1	SHROUD-FAN ASSM
8	566-1095-00	1	CONDENSER GROUP
36	577-0407-00	1	TANK-RECEIVER ASSM
57	912-3040-02	1	CONTACTOR KIT
55	921-0019-00	1	FAN MTR CONDUIT CONN KIT
51	985-CP2M-7K	1	CONTROL-DUAL PRESSURE
45	998-0161-01	1	SENTRONIC CONT MODULE
46	998-0162-00	1	SENTRONIC SENSOR KIT
56	998-0510-57	1	RECVR VALVE KIT 5/8 FL



## Looking for more information?

Visit us on the web at <http://www.artisan-scientific.com> for more information:

- Price Quotations
- Drivers
- Technical Specifications, Manuals and Documentation

## Artisan Scientific is Your Source for Quality New and Certified-Used/Pre-owned Equipment

- Tens of Thousands of In-Stock Items
- Hundreds of Manufacturers Supported
- Fast Shipping and Delivery
- Leasing / Monthly Rentals
- Equipment Demos
- Consignment

### Service Center Repairs

Experienced Engineers and Technicians on staff in our State-of-the-art Full-Service In-House Service Center Facility

### InstraView™ Remote Inspection

Remotely inspect equipment before purchasing with our Innovative InstraView™ website at <http://www.instraview.com>

### We buy used equipment! We also offer credit for Buy-Backs and Trade-Ins

Sell your excess, underutilized, and idle used equipment. Contact one of our Customer Service Representatives today!

Talk to a live person: 888-88-SOURCE (888-887-6872) | Contact us by email: [sales@artisan-scientific.com](mailto:sales@artisan-scientific.com) | Visit our website: <http://www.artisan-scientific.com>