18,000 to 25,000 BTUH

Cooling/Electric Heat

Room Air Accessories



REG-183J-20A 18,000 Nominal BTUH

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- · Energy saver mode, auto restart
- · Four-way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

Cooling Capacity BTUH	18,200/18,500
Approx. Sq. Ft. Cooling	700-1000
EER	9.7
Heating Capacity BTUH (electric)	9,100/11,200
Power Supply	208/230V 60Hz
Humidity Removal Pts/Hr	3.8
Ventilation Control	Yes
Fan Only	Yes
Fan Speeds Cool/Heat/Fan	3/3/3
Air Delivery Max. CFM	459
dB Level (hi/med/low)	61/58/55
Amps Cooling	9.1/8.4
Amps Heating	16.0/14.8
Maximum Fuse Size	20A
Power Cord	20A Tee NEMA 6-20P
Slide-Out Chassis	Yes
Window Mounting Kit	Yes
Remote Control	Yes
In-Home Service	Yes
Shipping Weight (lbs.)	127
Dimensions (in.) Height	17 ¹⁵ / ₁₆
Width	23 ⁵ /8
Depth	25 ⁷ / ₁₆



REG-253J 2

25,000 BTUH Nominal

FEATURES

- Electronic controls with full feature remote, 24-hour on/off timer
- · Energy saver mode, auto restart
- Four-way adjustable air direction
- One degree temperature adjustment
- Designed for supplemental electric heat only, thermostat cycles heating element on and off

SPECIFICATIONS

24,700/25,000
1400-1500
9.4
13,000/16,000
208/230V 60Hz
5.7
Yes
Yes
3/3/3
541
63/61/59
12.8/12.0
22.5/20.0
30A
30A Tandem NEMA 6-30P
Yes
Yes
Yes
Yes
142
18 ⁵ /8
26 ¹ / ₂
25 ¹ /2



AS080 & AS160

Window Support Brackets

Easy-to-install brackets add a full measure of safety to windowmounted air conditioners. Manufactured from heavy gauge steel with a durable baked-on epoxy finish, the brackets have stainless steel hardware to resist weather damage. Unique bubble level helps ensure proper installation angle.

- AS080—For room air conditioners up to 80 pounds
- AS160—For room air conditioners up to 160 pounds

EA448F Wall Sleeve

For BG and BGE Series

Sleeve is manufactured of G-90 steel and powder coated for durability and corrosion resistance; color matches unit color. The sleeve utilizes the aluminum back grille of the BG/BGE units, and front gaskets eliminate air see page.

IMPORTANT: Always wait to cut a hole in structure until unit arrives and dimensions can be verified.

EA448F—Wall Sleeve (inches) 15¹⁷/₃₂" H x 25⁷/₈" W x 16²³/₃₂" D