


CLOTH DUCT TAPE

VentureTape® 1557 is a high strength, premium quality polyethylene (PE) coated cloth duct tape coated with an aggressive rubber pressure sensitive adhesive. A versatile, high performing product, VentureTape 1557applies easily, will not curl when unwound and conforms well to irregular surfaces, providing superior performance and durability over a wide range of conditions.

Product Construction



Features & Benefits

- Versatile duct tape works well for vapor sealing, sheet metal ductwork and general purpose heavy duty applications
- Self wound product is hand tearable and applies easily
- Tears straight and will not curl when unwound
- Also excels in high heat and humidity conditions
- Conforms well to corners and irregular surfaces
- In stock product available for immediate delivery

Product Configurations

- Available in Black and Grey
- Standard roll size 2" x 60Y (50mm x 55m)

		Typical Value	Test
Test	Typical Value	(Metric)	Method
Product Thickness ^Ω	13.0 mils	0.33 mm	PSTC-133
Peel Adhesion △	50 oz/in	13.9 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	29 lb/in	131.1 N/25 mm	PSTC-131
Elongation	18 %	18 %	PSTC-131
Service Temperature	0 to 200 °F	-18 to 93 °C	
0 1 " "		1 00 1	

 $^{\Omega}$ - excluding liner

[∆] - 20 minute dwell

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076 From United Kingdom 0-800-962-957 From Australia 1-800-122-797 www.venturetape.com



GTA - NHT, Inc.
Venture Tape
30 Commerce Rd., Rockland, MA 02370
Tel 781-331-5900; Fax 781-871-0065
800-343-1076 (U.S.A.), 800-544-1024 (Canada)
Toll Free Fax 877-264-5490
www.venturetape.com

