

SUBMITTAL DATA FORM

UP TO 14 SEER / 2 TO 5 TONS

Job Name _____

Location _____

Purchaser _____

Order No. _____

Engineer _____

Unit No. _____

Model No. _____

Unit Designation _____

Performance Data Certified By: _____

Standard Features

- Energy-efficient compressor with internal relief valve
- PSC blower motor; EEM blower motor on 5-ton units
- Quiet horizontal discharge
- Copper tube/aluminum fin coil
- Totally enclosed, permanently lubricated condenser fan motor
- Fully charged system
- 5 kW to 20 kW electric heat kit available as a field-installed option
- AHRI Certified; ETL Listed

Cabinet Features

- Heavy-gauge galvanized-steel cabinet with attractive Architectural Gray powder-paint finish
- Fully insulated blower compartment has convenient access panels
- Louvered condenser coil protection
- One footprint; three heights



* Complete warranty details available from your local dealer or at www.goodmanmfg.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Québec.

PERFORMANCE DATA FOR SPLIT SYSTEM**Cooling Performance**

Total Capacity _____ MBH
Sensible Capacity _____ MBH
Outdoor Design TMP _____ °F DB / WB
Air Temp entering _____
Evaporator Coil _____ °F
Power Input Required _____ kW
(less blower motor)

Heating Performance

Total Heating Capacity _____ kW
_____ BTU/h

Supply Air Blower Performance

Total Supply Air _____ CFM
Ext. Static Pressure _____ IWG
Blower Speed _____ RPM
Power Output Required _____ BHP
Motor Ratings _____ HP
Power Input Required _____ kW

Electrical Data





Power Supply _____
Total Unit Amps _____

Max Overcurrent Device:

Fuse _____ Breaker _____ Amps _____

NOTES

DIMENSIONS



MODEL	DIMENSIONS					CHASSIS SIZE
	W"	D"	H"	A"	B"	
GPC1424H41**	66	33	30½	22	30	Small
GPC1430H41**	66	33	30½	22	30	Small
GPC1436H41**	66	33	30½	22	30	Small
GPC1442H41C*/D*	66	33	35½	24	35	Medium
GPC1442H41E*	66	33	30½	22	30	Small
GPC1448H41C*/D*	66	33	38½	24	38¾	Large
GPC1448H41E*	66	33	35½	24	35	Medium
GPC1460H41C*/D*	66	33	38½	24	38¾	Large
GPC1460H41E*	66	33	35½	24	35	Medium

ACCESSORIES

ACCESSORY DESCRIPTION	ITEM NUMBER		✓
	SMALL CHASSIS	MEDIUM/LARGE CHASSIS	
Downflow Economizer	PCE101	PCE102/103	
Downflow Plenum Kit	PCP101	PCP102/103	
Downflow Plenum Kit (R-8)	PCP101 R8	PCP102 R8 /103 RB	
Elbow Flashing w/ R-8 Liner	PCEF101	PCEF102/103	
Emergency Heat Relay	OT/EHR18-60	OT/EHR18-60	
External Horizontal Filter Rack	GPGHFR101	GPGHFR102/103	
Horizontal Economizer	DHZECNJP GCHM	DHZECNJP GCHL	
Manual Damper	PCMD101	PCMD102/103	
Horizontal Manual Damper	PCMDH101	PCMDH102/103	
Motorized Damper	PCMDM101	PCMDM102/103	
Outdoor Thermostat w/ Lockout Stat	OT18-60A	OT18-60A	
Roof Curb	PCCP101	PCCP102/103	
Square to Round	SQRPC101	SQRPC102/103	
Square to Round for Horizontal Application	SQRPCH101	SQRPCH102/103	

SINGLE-POINT KIT ACCESSORY KITS

Select the single-point kit accessory based on the unit model.

MODEL	SINGLE-POINT KIT
GPC1424***41C*	SPK-15
GPC1430***41C*	SPK-30
GPC1436***41C*	SPK-40
GPC1442***41C*	SPK-40
GPC1448***41C*	SPK-45
GPC1460***41C*	SPK-60

MODEL	SINGLE-POINT KIT
GPC1424***41D*	SPK-20
GPC1430***41D*	SPK-30
GPC1436***41D*	SPK-40
GPC1442***41D*	SPK-45
GPC1448***41D*	SPK-50
GPC1460***41D*	SPK-60