

ZR42K5E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

| | | |
|------------------------------|--------------|-------------|
| Evap(°F)/Cond(°F) | 45 / 130 | 50 / 100 |
| RG(°F)/Liq(°F) | 65.0 / 115.0 | 70.0 / 85.0 |
| Capacity (Btu/hr) | 42200 | 55900 |
| Power (Watts): | 3750 | 2540 |
| Current (Amps): | 11.25 | 8.60 |
| EER (Btu/Wh): | 11.25 | 21.95 |
| Mass Flow (lbs/hr): | 618 | 716 |
| Sound Power (dBA): | 73 Avg | 78 Max |
| Vibration (mils(peak-peak)): | 2.0 Avg | 3.0 Max |
| Record Date: | 2014-03-06 | |

Mechanical

| | | | |
|---|----------|-----------------------|---------|
| Number of Cylinders: | 0 | Displ(in^3/Rev): | 3.45 |
| Bore Size(in): | 0.00 | Displ(ft^3/hr): | 419.27 |
| Stroke(in): | 0.00 | | |
| Overall Length (in): | 9.69 | Mounting Length (in): | 7.50 |
| Overall Width (in): | 9.69 | Mounting Width (in): | 7.50 |
| Overall Height (in): | 19.94 | Mounting Height (in): | 17.17 * |
| Suction Size (in): | 7/8 Stub | | |
| Discharge Size (in): | 1/2 Stub | | |
| Oil Recharge (oz): | 34 | | |
| Initial Oil Charge (oz): | 42 | | |
| Net Weight (lbs): | 61 | | |
| Internal Free Volume (in^3): | 226.3 | | |
| Horse Power: | 3.5 | | |
| *Overall compressor height on Copeland Brand Product's specified mounting grommets. | | | |

Electrical

| | | | | | |
|---|------|------------------------|------|---------------|---------|
| LRA-High*: | 93.0 | MCC (Amps): | 20.0 | UL File No: | SA-2337 |
| LRA-Half Winding: | | RPM: | 3500 | UL File Date: | |
| LRA Low*: | | Max Operating Current: | 15.5 | | |
| RLA(=MCC/1.4;use for contactor selection): | 14.3 | | | | |
| RLA(=MCC/1.56;use for breaker & wire size selection): | 12.8 | | | | |
| *Low and High refer to the low and high nominal voltage ranges for which the motor is approved. | | | | | |

Alternate Applications

| Refrigerant | Freq (Hz) | Phase | Voltage | Application |
|-------------|-----------|-------|---------|------------------|
| R-407C HFC | 50 | 3 | 200/220 | Air Conditioning |
| R-22 HCFC | 50 | 3 | 200/220 | Air Conditioning |
| R-407C HFC | 60 | 3 | 200/230 | Air Conditioning |