Braeburn®

Wireless Setup Guide

BlueLink))
smart connect ™

Model 7500
Universal Programmable
Wireless Thermostat Kit

**Leave this Setup Guide
with thermostat.**

1 *Getting Started*

1.1 Install and wire the control module to the HVAC equipment *(see Installer Guide, Section 2, Part 1)*.

1.2 Install 2 supplied AA batteries into the thermostat *(See Installer Guide, Section 2, Part 4)*.

NOTE: Thermostat can be battery powered or 24 VAC powered (hardwired). If multiple wireless remote sensors are used, it is recommended to hardwire the thermostat.

2 Pair the Thermostat and Control Module

2.1 On the thermostat, press and hold down the **HOLD** and **RETURN** buttons for 3 seconds.

2.2 The word **CMOD** (control module) will appear in the display and the 🔊 symbol will flash *(see Figure 1)*.

NOTE: If the control module has already been paired, the 🔊 symbol will not be flashing. To reset wireless connection to control module, see Installer Guide, Section 4.

Figure 1

2.3 On the powered control module, press and hold the **CONNECT** button for 3 seconds *(see Figure 2)*.

2.4 The control module will enter pairing mode for 60 seconds. During this time the blue **COMM** indicator on the control module will flash once every 2 seconds.

2.5 Once successfully paired, the 🔊 symbol will stop flashing and the blue **COMM** indicator on the control module will turn on.

Connect Button

PWR   COMM

Figure 2

**2.6** Press **RETURN** on the thermostat at any time to exit.

NOTE: If pairing was unsuccessful, try moving the thermostat or repositioning the control module.

3 *Complete Installation*

3.1 Mount the thermostat *(see Installer Guide, Section 2, Parts 2-5)*.

3.2 If applicable, install and connect any wireless remote accessories *(see Accessory Manual)*.

3.3 Configure Thermostat Installer Settings based on your particular application *(see Installer Guide, Section 4)*.

3.4 If desired, adjust User Settings, Time of Day and Program Schedule *(see User Manual)*.

3.5 Test system *(see Installer Guide, Section 6)*.

Braeburn®

7500-105-01