

New Patented Cell Design

Features ActivePure® Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in "The Proof")

THE TECHNOLOGY

The Air Scrubber by Aerus® attaches directly to the HVAC system ductwork to reduce viruses, bacteria, and other contaminants in the ambient air and on surfaces while the HVAC fan is running. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2
- Staphylococcus Aureus
- · Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola

- Listeria monocytogenes
- Murine Norovirus
- E. coli
- · Candida auris
- · Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- · Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Air Scrubber by Aerus provides surface decontamination and air purification without the use of ozone while the HVAC system fan is running. It is a proactive and effective solution for your home or small business.

- Uses the latest version of ActivePure Technology
- Provides 24/7 surface decontamination and air purification¹
- Reduces allergens and other contaminants
- Protects your heating and cooling system from potential buildup
- New and Improved patented ActivePure Cell (Patent # 9867897)









Assembled in USA

Hall of Fame by





¹View test results at ActivePure.com/scientific-proof



SPECIFICATIONS

Product Information	9960052 Model: A1013U (Ozone Free) Model A1013U meets California ozone emissions limit. CARB Certified. 9960051 Model: A1013P NOTE: This unit does not meet California requirements and cannot be shipped in California
Technology Included	ActivePure® Technology
Electrical	Input Voltage: 24 Volts 1 Amp, 50/60 Hz Current: 17 Watts 'Conforms to UL STD 1598.
Mechanical	Distribution via air handler; Safety switch installed
Weight & Dimensions	3 pounds (1.2 kg.) 8.5" H x 8.5" W x 11" D (21.59 cm H x 21.59 cm W x 27.94 cm D)
Cell Dimensions	2.25" H x 2.25" W x 9" D (5.71 cm H x 5.71 cm W x 22.86 cm D)
Operating Temperature	34°F – 200°F (1.6°C - 93°C)
Coverage ¹	Up to 2,000 sq. ft. (185 m²) Nominal; 3,000 sq. ft. (279 m²) Maximum.
Warranty	Limited 5 year warranty; 2 year warranty on ActivePure Cell Assembly

	Contact Name:
<u></u>	Email:
	Phone Number:

^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.

