



A CSW Industrials Company

ZIPPTM II

Environmentally safer quick drying degreaser

Description

Zipptm II is an environmentally safer quick drying degreaser that removes grease, oil, wax, tar, gum, grime, dirt, carbon, and greasy stains from most hard surfaces. It will not short out electrical equipment. It may be used on oil burner parts, compressors, refrigeration units, greasy fan blades, strainers, engines, stoves, relay contact points, and electrical equipment.

Characteristics | Features

- Non-chlorinated
- Non-flammable & Non-conductive
- Excellent cleaner/degraser
- Fast Drying
- Contains no restricted solvents
- Leaves no residue

Applications

Zipptm II may be used on most dirty, greasy surfaces. It is great for use on electric motors, fan blades, compressors, all oil burner parts, strainers, engines, stoves, contact points, and refrigeration units

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
82645	12 ounce aerosol	12	13	0.52

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

DO NOT USE ON PLASTICS WITHOUT TESTING FIRST

1. Shake can well before using.
2. Thoroughly saturate part to be cleaned.
3. For heavy grease and grime deposits allow five minutes soaking time. Some agitation with a brush or rag is very helpful.
4. Allow to air dry.

For additional technical information, call Toll Free 1-800-231-3345

Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

WARNING!
CONTENTS UNDER PRESSURE.
VAPOR HARMFUL – KEEP OUT OF REACH OF CHILDREN
READ BACK PANEL CAREFULLY.

CONTAINS; CHLORINATED SOLVENTS. Use only as directed with adequate ventilation. Avoid contact with eyes and skin. Do not spray into fire or on hot surfaces. Store at room temperature. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120° F.

FIRST AID: Skin: Wash off with soap and water. **Eyes:** Flush with water for 15 minutes. Seek medical attention if irritation persists. **Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped, and oxygen if available. Call physician immediately.



WARNING: This product can expose you to chemicals including Propyl bromide, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

For additional information, refer to Safety Data Sheet.

Specifications

Wt/Gal @ 77°F	11.90 lbs/ gal.
Flash Point SETA CC	None
Color	Clear
Odor	Sweet
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by
RectorSeal, LLC
2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • Fax 713-263-7577
Toll-free 800-231-3345 • Fax 800-441-0051