



A CSW Industrials Company

PRODUCT DATA SHEET

D-FACTOR™

High strength cleaner & degreaser

Description

D-Factor is an extra strong, heavy duty cleaner. Detergent-based formula rapidly removes grime, oil, grease and dust. Low foaming action cleans grease and dust from surfaces which are normally inaccessible. D-Factor is biodegradable and can be used for cleaning electronic and permanent air filters and all mechanical equipment. D-Factor's maximum degreasing, high strength cleaning formula is self-rinsing and suitable for both condenser and evaporator coils.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE



Directions for Use:

1. Appropriately dilute with water for economic use.
 - For extremely dirty coils/equipment** - 1 part D-FACTOR to 4 parts water.
 - For cleaning all types of filters** - 1 part D-FACTOR to 4 parts water.
 - For medium dirty coils** -1 part D-FACTOR to 6 parts water.
 - For light dirt removal** -1 part D-FACTOR to 8 parts water.
 - For no-rinse indoor coils** -1 part D-FACTOR to 40 parts water.
2. Shut off system.
3. Apply the diluted solution with a trigger sprayer, hand powered tank or high pressure washer. Use a brush to help faster penetration of hard, encrusted dirt.
4. Allow 5 to 15 minutes soaking time before rinsing. On an operating evaporator coil, rinsing is not required since the condensate will flush out all the loosened slime and dirt.
5. For condenser coils, rinse coil thoroughly with low-pressure washer. Repeat if necessary.

Characteristics | Features

- Max degreasing strength
- High cleaning strength
- Biodegradable*
- Low foaming
- Concentrated – dilute with water for economical use
- Will not harm copper or aluminum
- Multipurpose

*Contains the best available biodegradable surfactants and detergents

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
11060	Gallon (3.8 L)	4 Bottles	45	1.21

D-FACTOR™

High strength cleaner & degreaser

Specifications

Wt/Gal @ 77°F 10 lbs./gal.

Flash Point None

Color Yellow

Shelf Life 2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

3255 Wyandotte St. East • Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R50400-0323