



A CSW Industrials Company

PRODUCT DATA SHEET

GRIME-SOLV™

Foaming, heavy duty cleaner & degreaser

Description

GRIME-SOLV™ is a foaming, heavy duty, cleaner and degreaser, for use on marine and automotive engines, heating, air conditioning and refrigeration equipment, and all types of machinery that can be rinsed with water or wiped with a rag. The foam holds the cleaning agents where sprayed, concentrating the powerful emulsifiable chemicals to lift off dirt and grease.

Application

GRIME-SOLV™ lifts encrusted grime, grease or carbon from oil burning , air conditioning and refrigeration equipment, marine and automotive engines and other machinery that can be rinsed with water or wiped with a rag. Can be used to remove stains from concrete driveways and brick walls, to clean white wall tires, and for cleaning surfaces before painting.



Characteristics | Features

- Non-flammable
- Non-corrosive
- Excellent cleaner/degreaser
- Safe for metals
- Wipes clean or rinses with water

Packaging

Code	Size	Qty per Case	Lbs. per Case	Cubic Ft per Case
88436	14 ounce aerosol	12	14	0.52

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

- SHAKE WELL BEFORE USING.
- Spray from 6 to 10 inches away and thoroughly saturate areas to be cleaned. Faster action is obtained by gently brushing GRIME-SOLV™ into the grease and grime being removed. Brushing is essential on unusually heavy deposits.
- Allow GRIME-SOLV™ to penetrate for a short time.
- Flush off with water – the stronger the stream the better. When hosing down engines, be certain to start the engine as soon as possible and idle until the engine becomes warm enough to evaporate the water.
- If used on painted surfaces, wash GRIME-SOLV™ off immediately to avoid removing the wax finish or streaking the paint.
- Test on plastic surfaces prior to use. Product will damage certain plastics.

For additional technical information, call Toll Free 1-800-231-3345

Precautions

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet.

Specifications

Wt/Gal @ 77°F	11.04 lbs/ gal
Flash Point SETA CC	None
Color	White foam
Shelf Life	2 years minimum

NOT FOR SALE IN CALIFORNIA

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty

For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au

3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2023 RectorSeal. All rights reserved. R50192-1023