



Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left-hand refrigerant and plumbing connections, with downturn suction line for easy installation in manufactured housing applications.
- Downflow plates and manufactured housing drain hose included.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 - 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Liquid line Schrader valve for coil pressurization-confirmation testing.
- Heavy duty polypropylene drain pans.
- Drain connection: 177L pans have single LH 3/4" FPT, 195L pans have quad drains, 3/4" FPT.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com.

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE R 410-A	DIMENSIONS			SHIPPING INFORMATION			
			PAN WIDTH (W)"	PAN DEPTH (D)"	COIL BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
CM24A(2,3)*	24,000	0.055	17-3/4	19-5/8	13-1/2	17	27	N/A	30
CM24B(2,3)*		0.055	17-3/4	19-5/8	15-1/2	20	31	N/A	25
CM24C(2,3)*		0.055	17-3/4	19-5/8	17-1/2	23	36	N/A	25
CM24D(2,3)*		0.055	17-3/4	19-5/8	19-1/2	25	40	N/A	20
CM30A(2,3)*	30,000	0.059	17-3/4	19-5/8	15-1/2	20	31	N/A	25
CM30B(2,3)*		0.059	17-3/4	19-5/8	17-1/2	23	36	N/A	25
CM30C(2,3)*		0.059	17-3/4	19-5/8	19-1/2	25	40	N/A	20
CM36A(2,3,4)*	36,000	0.068	17-3/4	19-5/8	17-1/2	23	36	47	25
CM36B(2,3,4)*		0.068	17-3/4	19-5/8	19-1/2	25	40	53	20
CM36C34*		N/A	N/A	23	26	N/A	25	N/A	14
CM42A(2,3)*	42,000	0.074	17-3/4	19-5/8	19-1/2	25	40	55	20
CM42A4*		0.074	17-3/4	19-1/2	17-1/2	N/A	N/A	50	25
CM48A3*	48,000	0.080	17-3/4	19-5/8	21-1/2	N/A	45	60	16
CM48A4*		0.080	17-3/4	19-1/2	21-1/2	N/A	45	60	16
CM48B3*		0.080	17-3/4	19-5/8	23-1/2	N/A	49	63	12
CM48B4*		0.080	17-3/4	19-1/2	23-1/2	N/A	49	63	12
CM48C3*		0.080	17-3/4	19-5/8	25-1/2	N/A	54	68	12
CM48C4*		0.080	17-3/4	19-1/2	25-1/2	N/A	54	68	12
CM48D3*		0.080	17-3/4	19-5/8	27-1/2	N/A	58	72	12
CM48D4*		0.080	17-3/4	19-1/2	27-1/2	N/A	58	72	12
CM48E3*		0.080	17-3/4	19-5/8	19-1/2	N/A	40	55	20
CM48E4*		0.080	17-3/4	19-1/2	19-1/2	N/A	40	55	20
CM59A4*	60,000	0.089	17-3/4 - 19-1/2	19-1/2	19-1/2	34	54	70	12
CM60A3*		0.089	19-1/2	19-1/2	25-1/2	37	58	76	12
CM60A4*		0.089	19-1/2	19-1/2	25-1/2	38	60	79	12
CM60B3*		0.089	19-1/2	19-1/2	27-1/2	41	65	86	12
CM60B4*		0.089	19-1/2	19-1/2	27-1/2	46	73	95	12

Notes: Use metal drain pan on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°