

**BOSS<sup>®</sup>**  
**PRO****WEATHER  
PROOF SEAL****370**  
**SILICONE**

# HVAC PROFESSIONAL GRADE

**BOSS<sup>®</sup>370**

HVAC Silicone is a one-part acetoxy cure adhesive sealant that is suitable for general heating, ventilation and air conditioning sealing and adhesive applications. This product will adhere to clean metal, glass, many types of wood, silicone resins, vulcanized silicone rubber, ceramics and plastic surfaces. A primer may be required for optimum adhesion to some substrates.

**COLORS:****Cartridge**

- 142273- Clear
- 142275 - White
- 142272- Black
- 142271 - Aluminum

**Pressure Can**

- 143096 - Clear
- 143097 - White
- 143095 - Aluminum

**FEATURES:**

- VOC Compliant
- Plastic cartridge or pressure can
- Weatherproof Seal
- Fast Cure
- Meets TT-S-001543A, TT-S-00230C, and ASTM C-920-86

**THE IDEAL SEALANT/ADHESIVE FOR:**

- General Heating
- Vents
- Air Conditioning
- Ducts
- Fixtures
- Piping
- Wood, Metal, & Glass
- Electrical Connections
- Silicone Resins
- Vulcanized Silicone Rubber
- Ceramics
- Plastic Surfaces
- Many More...

**PACKAGING:**

- 10.1 oz. Cartridge
- 8 oz. Pressure Can
- 4.5 Gallon Pail
- Other sizes available upon request

Scan the QR Code to see the full line of **BOSS<sup>PRO</sup>** Products!



Visit Our Website

[www.bossproducts.com](http://www.bossproducts.com)

**BOSS<sup>®</sup>**  
**PRO****WEATHER  
PROOF SEAL****370**  
**SILICONE**

# HVAC

## PROFESSIONAL GRADE

### TYPICAL PROPERTIES

#### Uncured

Colors (cartridge)	clear, white, black, aluminum
Colors (pressure can)	clear, white, aluminum
Custom colors upon request	
Slump	NIL
Tack-Free Time	(77°F & 50% RH)
10 - 20 minutes Extrusion Rate	350 gr/min.

#### Cured-Physical 7 Days at 77°F (25°C) and 50% RH (1/8" thickness)

Elongation	500
Durometer, Shore A	25
Tensile Strength	350 psi
Movement Capability	±25%
Service Temperature	-40°F to 400°F
Application Temperature	35°F to 140°F

\*These values may vary depending on environmental factors such as temperature, humidity, and type of substrate.

Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Soudal Accumetric.

#### LIMITATIONS

- Do not use for structural glazing
- It is the sole responsibility of the user to test the adhesion to the substrate for suitability

#### CAUTION

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. OVEREXPOSURE TO VAPOR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use only outdoors or in a well ventilated area. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. KEEP OUT OF THE REACH OF CHILDREN. For safe handling information on this product, consult the Safety Data Sheet (SDS).

  
Soudal Accumetric

Call The  
**BOSS<sup>®</sup>**

**800-928-BOSS**

350 Ring Road • Elizabethtown • KY 42701  
(270) 769-3385 • 800-928-2677 • Fax: (270) 765-2412  
[www.bossproducts.com](http://www.bossproducts.com)