



# Safety Data Sheet

## BOSS® 370 HVAC Silicone

### Section 1. Identification

Product Identifier	BOSS® 370 HVAC Silicone		
Synonyms	37003; 37002; 37001; 37000; 02260CL10; 02260WH10; 02260BK10; 02260AL10		
Manufacturer Stock Numbers	02260CL10; 02260WH10; 02260BK10; 02260AL10		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact			
Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	N/A
Precautionary Statements	
Response	N/A
Prevention	Use only outdoors or in a well-ventilated area.
Storage	N/A
Disposal	N/A

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

GHS Classification Not a hazardous substance or mixture.

GHS Label Element Not a hazardous substance or mixture.

Other hazards None known

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
64742-46-7	Distillates (petroleum), hydrotreated middle	20% - 30%
7631-86-9	Amorphous silica	5% - 10%

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First-Aid Measures

**Eye Contact** Rinse with water for 15 minutes. Obtain medical attention.

**Skin Contact** Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

**Inhalation** Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor are generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.

**Ingestion** Get immediate medical attention. Only induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person.

**Comments** Treat according to person's condition and specifics of exposure.

### Section 5. Fire Fighting Measures

**Suitable Extinguishing Media** N/A

**Unsuitable Extinguishing Media** N/A

**Auto-ignition Temperature** Not determined

**Extinguishing Media** On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

**Flammability Limits in Air** Not determined

**Special Fire Fighting Procedures** Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire or Explosion Hazards None known

Hazardous Decomposition Products Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:

Carbon oxides and traces of incompletely burned carbon compounds  
Formaldehyde  
Silicon dioxide

Depending on color, may also evolve:  
Metal oxides

## Section 6. Accidental Release Measures

**Steps to be taken in case of spill or release** Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

## Section 7. Handling and Storage

**Storage** Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

**Handling** Use adequate ventilation. Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Avoid breathing vapors, mist, dust or fumes. Keep container closed. Do not take internally.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Amorphous silica	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup>	Not Est.

**Personal Protective Equipment** Goggles, Gloves

Exposure Controls	Acetic acid is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 10 ppm and ACGIH TLV: TWA 10 ppm, STEL 15 ppm.
Engineering Controls	Local Ventilation: Recommended General Ventilation: Recommended
Eye Protection	Safety goggles or glasses with side shields are recommended.
Skin Protection	Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.
Respiratory Protection	<p>Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.</p> <p>Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.</p> <p>Suitable Respirator: Respiratory protection is not needed under ambient conditions.</p> <p>If vapor/mist/dust/fumes are generated when material is heated or handled, respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirator. Protection provided by air purifying respirators against exposure to any hazardous chemical limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure level are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.</p>
Precautionary Measures	Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust or fumes. Keep container closed. Do not take internally. Use reasonable care.
Comment	Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.
Note	When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.
Note	These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

<b>Section 9. Physical and Chemical Properties</b>
--

Physical State	Paste
Color	Refer to product label
Odor	Acetic Acid Odor
Odor Threshold	N/A
Solubility	Not Determined
Partition coefficient Water/n-octanol	N/A



Water Treatment Plants	
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

## Section 13. Disposal

**Waste Disposal Method** We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.

## Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
<b>TSCA Status</b>	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
<b>SARA Title III Section 302 Extremely Hazardous Substances</b>	None
<b>SARA Title III Section 304 CERCLA Substances dangereuses</b>	None
<b>SARA Title III Section 312 Hazard Class</b>	Acute: Yes Chronic: No Fire: No Pressure: No Reactive: No
<b>SARA Title III Section 313 Toxic Chemicals</b>	None present or none present in regulated quantities.
<b>Note</b>	Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

California Proposition 65	This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: None known
Massachusetts	Silica, amorphous (7631-86-9)  Depending on color, may also contain: Titanium dioxide (13463-67-7)
New Jersey	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Ethyltriacetoxysilane (17689-77-9) Hydrotreated medium petroleum distillates (64742-46-7) Methyltriacetoxysilane (4253-34-3) Silica, amorphous (7631-86-9)  Depending on color, may also contain: Carbon black (1333-86-4) Titanium dioxide (13463-67-7)
Pennsylvania	Dimethyl siloxane, hydroxy-terminated (70131-67-8) Hydrotreated medium petroleum distillates (64742-46-7) Silica, amorphous (7631-86-9)  Depending on color, may also contain: Titanium dioxide (13463-67-7)

<b>Section 16. Other Information</b>
--------------------------------------

Revision Date	8/12/2016
Disclaimer	The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.



# Safety Data Sheet

## BOSS® 370 HVAC Silicone Sealant Pressure Can

### Section 1. Identification

Product Identifier	BOSS® 370 HVAC Silicone Sealant Pressure Can		
Synonyms	37008; 04369CL10		
Manufacturer Stock Numbers	04369CL10		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact Address	Soudal Accumetric 350 Ring Road Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

### Section 2. Hazards Identification

Classification	EYE DAMAGE/IRRITATION - Category 2A GASES UNDER PRESSURE - Liquefied gas SKIN CORROSION/IRRITATION - Category 2
Signal Word	Warning

## Pictogram



## Hazard Statements

Causes serious eye irritation  
Causes skin irritation  
Contains gas under pressure; may explode if heated

## Precautionary Statements

### Response

If eye irritation persists: Get medical advice/attention.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If medical advice is needed, have product container or label at hand.  
If on skin: Wash with plenty of soap and water.  
If skin irritation occurs: Get medical advice/attention.  
Take off contaminated clothing and wash it before reuse.

### Prevention

Wash thoroughly after handling.  
Wear eye protection/face protection.  
Wear protective gloves.

### Storage

Protect from sunlight. Store in a well-ventilated place.

### Disposal

Dispose of contents/container in accordance with local, regional, national and international regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Additional Information None known

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
7631-86-9	Amorphous silica	5% - 10%
64742-46-7	Distillates (petroleum), hydrotreated middle	20% - 30%
75-37-6	Difluoroethane (propellant)	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

### Description of necessary first aid measures

Eye Contact  
Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### Skin Contact

Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

### Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Eye contact

Causes serious eye irritation.

### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

### Ingestion

Irritating to mouth, throat and stomach.

### Skin contact

Causes skin irritation.

### Eye contact

Adverse symptoms may include the following:  
pain or irritation, watering, redness

### Inhalation

No known significant effects or critical hazards.

### Skin contact

Adverse symptoms may include the following:  
irritation, redness

Potential acute health effects

Over-exposure signs/symptoms

Indication of immediate medical attention and special treatment needed

Ingestion  
No known significant effects or critical hazards.

Notes to physician  
In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments  
No specific treatment.

Protection of first-aiders  
No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Note See toxicological information (Section 11).

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable Extinguishing Media None known

Specific hazards arising from the chemical No specific fire or explosion hazard.

Hazardous thermal decomposition products Decomposition products may include the following materials: carbon dioxide, carbon monoxide, halogenated compounds, carbonyl halides, metal oxide/oxides

Special protective actions for fire fighters No special precaution is required.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures For non-emergency personnel:  
No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:  
If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

### Small spill

Move containers from spill area. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

### Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Do not dry sweep. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and Storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Amorphous silica	10 mg/m <sup>3</sup>	6 mg/m <sup>3</sup>	Not Est.
Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Difluoroethane (propellant)	Not established	Not established	N/A

### Personal Protective Equipment

Goggles, Gloves

Appropriate engineering controls

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or gases. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to product label
Odor	Acetic acid
Odor Threshold	No data available
Solubility	No data available

Partition coefficient Water/n-octanol	No data available
VOC%	24 g/L
Viscosity	Not applicable
Specific Gravity	0.96
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not applicable
FP Method	N/A
pH	Not applicable
Melting Point	No data available
Boiling Point	Not applicable
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not applicable
Flammability	Not classified as a flammability hazard
Decomposition Temperature	No data available
Auto-ignition Temperature	No data available
Vapor Pressure	Not applicable
Vapor Density	No data available

**Note** The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.

Incompatible materials Reactive or incompatible with the following materials: oxidizing materials.  
Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological Information

Information on toxicological effects Acute toxicity:  
There is no data available.

Irritation/corrosion:  
There is no data available.

Sensitization:  
There is no data available.

Mutagenicity:  
There is no data available.

Carcinogenicity:  
There is no data available.

Reproductive toxicity:  
There is no data available.

Teratogenicity:  
There is no data available.

Specific target organ toxicity (single exposure):  
There is no data available.

Specific target organ toxicity (repeated exposure):  
There is no data available.

Aspiration hazard:  
There is no data available.

Information on the likely routes of exposure Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects Eye contact  
Causes serious eye irritation

Inhalation  
Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact  
Causes skin irritation.

Ingestion  
Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact  
Adverse symptoms may include the following:  
pain or irritation, watering, redness

Inhalation  
No known significant effects or critical hazards.

Skin contact  
Adverse symptoms may include the following:  
irritation, redness

Ingestion  
No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term

Short term exposure  
Potential immediate effects: No known significant effects or critical hazards.  
Potential delayed effects: No known significant effects or critical hazards.

Long term exposure  
Potential immediate effects: No known significant effects or critical hazards.  
Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General:  
No known significant effects or critical hazards.

Carcinogenicity:  
No known significant effects or critical hazards.

Mutagenicity:  
No known significant effects or critical hazards.

Teratogenicity:  
No known significant effects or critical hazards.

Developmental effects:  
No known significant effects or critical hazards.

Fertility effects:  
No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates: There is no data available.

## Section 12. Ecological Information

Toxicity  
There is no data available.

Persistence and degradability  
There is no data available.

Bioaccumulative potential  
There is no data available.

Other adverse effects  
No known significant effects or critical hazards.

## Section 13. Disposal

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## Section 14. Transport Information

### UN Number

1950

### UN Proper Shipping Name

Aerosols, flammable (each not exceeding 1 L capacity) (1,1-Difluoroethane)

### DOT Classification

Transport hazard class: 2.1

### Packing Group

-

### Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

## Section 15. Regulatory Information

### United States inventory (TSCA 8b)

All components are listed or exempted.

### Clean Air Act (CAA)

Section 112 Regulated Flammable Substances  
1,1-Difluoroethane

Section 112 (b) Hazardous Air Pollutants (HAPs)  
Not listed

Section 602 Class I Substances  
Not listed

Section 602 Class II Substances  
Not listed

## SARA

SARA 302/304  
Composition/information on ingredients  
No products were found.

SARA 304 RQ  
Not applicable

SARA 311/312 Classification  
Sudden release of pressure  
Immediate (acute) health hazard

## State Regulations

Massachusetts  
The following components are listed: Silicon dioxide; 1,1-Difluoroethane

New York  
None of the components are listed.

New Jersey  
The following components are listed: 1,1-Difluoroethane

Pennsylvania  
The following components are listed: Silicon dioxide

## Chemical Weapons Convention List

Schedule I  
Not listed

Schedule II  
Not listed

Schedule III  
Not listed

## California Prop 65

Clear  
This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Black  
WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Other Colors  
WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## Section 16. Other Information

Revision Date

6/1/2018

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine

that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.