

ZP54K5E-TFDHFC, R-410A, 60 Hz, 3 - Phase, 460 V [Also Available with Variable Frequency Drives](#)**Air Conditioning**

Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Copeland Wholesaler. Please check with your local Copeland Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in^3/Rev):	3.12
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.46
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69
Capacity (BTU/hr)	54300	73800	Overall Height (in):	16.46
Power (W):	5070	3400	Mounting Length (in):	7.50
Current (Amps):	7.2	4.9	Mounting Width (in):	7.50
EER(BTU/Wh):	10.7	21.7	Mounting Height (in):	17.20
Mass Flow (lbs/hr):	799	907	Suction Size (in),Type:	7 / 8 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	71 Avg	76 Max	Initial Oil Charge (oz):	42
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	36
Record Date:	2017-03-01		Oil Type:	3MA
			Net Weight (lbs):	71.4
			Internal Free Volume (in^3):	190.8
*Overall compressor height on Copeland Brand Product's specified mounting grommets.				
Electrical			Capacitors	
LRA High* (Amps):	52		Type	Part No
LRA Low*(Amps):	No data available in table			
LRA Half Winding (Amps):				
MCC (Amps):	12.1			
Max Operating Current (Amps):	10.30			
RLA, MCC/1.4(use for contactor selection)(Amps):	8.6			
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	7.8			
RPM:	3500			
Box IP :	21			
UL File No:	SA2337-20031217			
UL File Date:	2014-03-21			

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	380/420	3	50	Air Conditioning