

ZP51LXE-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V . [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Copeland Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	50	Displacement (in ³ /Rev):	2.94	
Condensing Temp. (°F)	130.00	100	Displacement (ft ³ /Hr):		
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.69	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69	
Capacity (BTU/hr)	52500	70500	Overall Height (in):	16.46	
Power (W):	4850	3260	Mounting Length (in):	7.50	
Current (Amps):	13.6	9.8	Mounting Width (in):	7.50	
EER(BTU/Wh):	10.8	21.7	Mounting Height (in):	17.20	
Mass Flow (lbs/hr):	765	865	Suction Size (in),Type:	7 / 8 Stub	
Sound Data @ 50 / 115			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	71 Avg	76 Max	Initial Oil Charge (oz):	42	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	36	
Record Date:	2025-07-16		Oil Type:	3MA	
			Net Weight (lbs):	71.7	
			Internal Free Volume (in ³):	*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	110	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	24.9					
Max Operating Current (Amps):	19					
RLA, MCC/1.4(use for contactor selection)(Amps):	17.8					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	16.0					
RPM:	3500					
Box IP :	21					
UL File No:	SA2337-20031217					
UL File Date:	2014-03-21					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/230	3	50	Air Conditioning