

## PolarPad™ Heavy Duty HVAC Pads

Condenser installations begin better with PolarPad. The PolarPad is engineered and designed as a base for HVAC equipment. The plastic pad is injection molded from high density polyethylene (HDPE), which is durable, strong, and lightweight. The unique design has strong, uniform ribbing along the underside. The pad is molded with a texture along the top, and rounded edges on the sides to give a clean concrete look and feel. The PolarPad is best used as a base for light, ground supported equipment such as air conditioning condensers, swimming pool filters and heat pumps. Pads must be fully supported across the bottom, and set on compacted soil, hard surface, or gravel.

### Features & Benefits

- Strong, Durable & Impact Resistant
- Engineered & Designed to Resist Cracking, Breaking & Warping
- Always Flat, Self-Leveling Design
- Reinforced, Uniform Ribbing
- Reduced Sharp Edges, Corners
- Reinforced Sidewalls, Wear Areas
- Supports Over 40 lbs / sq ft
- Corner Bracing Protects Against Mowers & Weed Eaters
- Weather, Temperature & UV Resistant
- Textured Surfaces for Enhanced Traction
- Resistant to Oils, Refrigerants & Canine Urine
- Pad Size Stamped on Every Part
- ASTM Standards
- Lightweight, Easy to Handle
- One Person Installation, No Additional Equipment Required
- Available in Black & Gray
- Available in Both 2" & 3" Profiles\*
- In Stock & Ready to Ship



Limited Warranty

For more information on our product warranty, visit [rectorseal.com](http://rectorseal.com).



**Package Unit Sizes Are Available:**  
36x54x3, 48x48x3, 52x52x3, 45x58x3

- Tested at a Third-party Laboratory for Overall Strength and Durability
- Manufactured with Resin that Meets the Below Standards:
  - ASTM D4976 – PE233
  - FDA 21 CFR 177.1520(c) 3.2a, use conditions B through H per 21 CFR 176.170(c)

| Model         | Color | Size:<br>W x L x H (in) | Weight<br>(lbs) | Maximum<br>Load (lbs) | Pallet<br>Quantity | Temperature Range |
|---------------|-------|-------------------------|-----------------|-----------------------|--------------------|-------------------|
| POLAR1838-3B  | BLACK | 18 X 38 X 3             | 8.9             | 1250**                | 32                 | -60°F to +180°F   |
| POLAR1838-3GY | GRAY  | 18 X 38 X 3             | 8.9             | 1250**                | 32                 | -60°F to +180°F   |
| POLAR2424-2B  | BLACK | 24 X 24 X 2             | 6.0             | 1210**                | 64                 | -60°F to +180°F   |
| POLAR2424-2GY | GRAY  | 24 X 24 X 2             | 6.0             | 1210**                | 64                 | -60°F to +180°F   |
| POLAR2424-3B  | BLACK | 24 X 24 X 3             | 7.4             | 1260**                | 64                 | -60°F to +180°F   |
| POLAR2424-3GY | GRAY  | 24 X 24 X 3             | 7.4             | 1260**                | 64                 | -60°F to +180°F   |
| POLAR2436-3B  | BLACK | 24 X 36 X 3             | 11.0            | 1300**                | 32                 | -60°F to +180°F   |
| POLAR2436-3GY | GRAY  | 24 X 36 X 3             | 11.0            | 1300**                | 32                 | -60°F to +180°F   |
| POLAR2448-3B  | BLACK | 24 X 48 X 3             | 13.6            | 1400**                | 32                 | -60°F to +180°F   |
| POLAR2448-3GY | GRAY  | 24 X 48 X 3             | 13.6            | 1400**                | 32                 | -60°F to +180°F   |
| POLAR3030-2B  | BLACK | 30 X 30 X 2             | 8.6             | 1250**                | 23                 | -60°F to +180°F   |
| POLAR3030-2GY | GRAY  | 30 X 30 X 2             | 8.6             | 1250**                | 23                 | -60°F to +180°F   |
| POLAR3030-3B  | BLACK | 30 X 30 X 3             | 12.4            | 1300**                | 16                 | -60°F to +180°F   |
| POLAR3030-3GY | GRAY  | 30 X 30 X 3             | 12.4            | 1300**                | 16                 | -60°F to +180°F   |
| POLAR3040-3B  | BLACK | 30 X 40 X 3             | 16.2            | 1700**                | 16                 | -60°F to +180°F   |
| POLAR3040-3GY | GRAY  | 30 X 40 X 3             | 16.2            | 1700**                | 16                 | -60°F to +180°F   |
| POLAR3232-2B  | BLACK | 32 X 32 X 2             | 9.7             | 1480**                | 23                 | -60°F to +180°F   |
| POLAR3232-2GY | GRAY  | 32 X 32 X 2             | 9.7             | 1480**                | 23                 | -60°F to +180°F   |
| POLAR3232-3B  | BLACK | 32 X 32 X 3             | 13.0            | 1440**                | 16                 | -60°F to +180°F   |
| POLAR3232-3GY | GRAY  | 32 X 32 X 3             | 13.0            | 1440**                | 16                 | -60°F to +180°F   |
| POLAR3636-2B  | BLACK | 36 X 36 X 2             | 12.3            | 1540**                | 23                 | -60°F to +180°F   |
| POLAR3636-2GY | GRAY  | 36 X 36 X 2             | 12.3            | 1540**                | 23                 | -60°F to +180°F   |
| POLAR3636-3B  | BLACK | 36 X 36 X 3             | 16.1            | 1500**                | 16                 | -60°F to +180°F   |
| POLAR3636-3GY | GRAY  | 36 X 36 X 3             | 16.1            | 1500**                | 16                 | -60°F to +180°F   |
| POLAR3648-3B  | BLACK | 36 X 48 X 3             | 21.3            | 1850**                | 16                 | -60°F to +180°F   |
| POLAR3648-3GY | GRAY  | 36 X 48 X 3             | 21.3            | 1850**                | 16                 | -60°F to +180°F   |
| POLAR3654-3B  | BLACK | 36 X 54 X 3             | 26.0            | 1720**                | 16                 | -60°F to +180°F   |
| POLAR3654-3GY | GRAY  | 36 X 54 X 3             | 26.0            | 1720**                | 16                 | -60°F to +180°F   |
| POLAR3842-3B  | BLACK | 38 X 42 X 3             | 18.2            | 1700**                | 16                 | -60°F to +180°F   |
| POLAR3842-3GY | GRAY  | 38 X 42 X 3             | 18.2            | 1700**                | 16                 | -60°F to +180°F   |
| POLAR4040-3B  | BLACK | 40 X 40 X 3             | 18.0            | 1710**                | 16                 | -60°F to +180°F   |
| POLAR4040-3GY | GRAY  | 40 X 40 X 3             | 18.0            | 1710**                | 16                 | -60°F to +180°F   |
| POLAR4558-3B  | BLACK | 45 X 58 X 3             | 36.5            | 2050**                | 16                 | -60°F to +180°F   |
| POLAR4558-3GY | GRAY  | 45 X 58 X 3             | 36.5            | 2050**                | 16                 | -60°F to +180°F   |
| POLAR4848-3B  | BLACK | 48 X 48 X 3             | 32.0            | 1900**                | 16                 | -60°F to +180°F   |
| POLAR4848-3GY | GRAY  | 48 X 48 X 3             | 32.0            | 1900**                | 16                 | -60°F to +180°F   |
| POLAR5252-3B  | BLACK | 52 X 52 X 3             | 37.5            | 2100**                | 16                 | -60°F to +180°F   |
| POLAR5252-3GY | GRAY  | 52 X 52 X 3             | 37.5            | 2100**                | 16                 | -60°F to +180°F   |

**Disclaimer:** \*\*Load should be distributed evenly across pan or pad surface to give maximum allowable load rating.

**Exclusions or Limitations:** PolarPad equipment pads are designed and manufactured to be used as bases or light, ground supported equipment such as air conditioning condensers, swimming pool filters and heat pumps. Use of PolarPad pads for purposes other than those listed above or improper installation of PolarPad pads may result in pan failure. DuraPlas disclaims any liability due to such misuses or improper installation.