

SCROLL COMPRESSOR



ZR SERIES, 1 1/2 TO 25 HP

- Suitable for air conditioning applications.
- **Capacitor** required, not provided
- **(Bold) Connection** = Rotolock valve, adapter required (961,965 suffix)
- ZR54K3E compressor has R407C applications; KCE compressors have R407C and R134a applications



Part No.	Refrig	Capacity		RLA (Amps)	Run Capacitor (µf x Voltage)	Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
		(BTUH)	Voltage					Suction	Discharge		
ZR16K5PFV800	R22	15500	208-230/1/60	9.3	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	53.0	791.10
ZR16K5EPFV800	R407C, R22	15500	208-230/1/60	9.3	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	53.0	827.10
ZR16K5EPFJ800	R407C, R22	15,500	265/1/60	8.9	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	53.0	882.00
ZR18K5PFV800	R22	18,000	208-230/1/60	10.7	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	48.6	810.90
ZR18K5EPFV800	R407C, R22	18,000	208-230/1/60	10.7	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	48.6	828.00
ZR18K5EPFJ800	R407C, R22	18,000	265/1/60	8.9	30 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	48.6	882.90
ZR21K5PFV800	R22	21,000	208-230/1/60	12.0	35 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	47.0	816.30
ZR21K5TF5800	R22	21,000	200-230/3/60	8.6	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.9	972.00
ZR21K5TFD800	R22	21,000	460/3/60	4.3	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.9	972.00
ZR21K5EPFV800	R407C, R22	21,000	208-230/1/60	12.0	35 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	47.0	830.70
ZR21K5EPFJ800	R407C, R22	21,000	265/1/60	10.4	35 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	47.0	885.60
ZR21K5ETF5800	R407C, R22	21,000	200-230/3/60	8.6	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.9	989.10
ZR21K5ETF800	R407C, R22	21,000	460/3/60	4.3	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.9	989.10
ZR25K5PFV800	R22	25,300	208-230/1/60	15.0	40 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	50.0	839.70
ZR25K5TF5800	R22	25,300	200-230/3/60	8.9	—	7.5 x 7.5	15.86	3/4 S	1/2 S	49.1	999.90
ZR25K5TFD800	R22	25,300	460/3/60	4.6	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.8	999.90
ZR25K5EPFV800	R407C, R22	25,300	208-230/1/60	15.0	40 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	50.0	854.10
ZR25K5EPFJ800	R407C, R22	25,300	265/1/60	12.1	35 x 440	7.5 x 7.5	15.86	3/4 S	1/2 S	50.0	910.80
ZR25K5ETF5800	R407C, R22	25,300	200-230/3/60	8.9	—	7.5 x 7.5	15.86	3/4 S	1/2 S	49.1	1017.00
ZR25K5ETF800	R407C, R22	25,300	460/3/60	4.6	—	7.5 x 7.5	15.86	3/4 S	1/2 S	48.8	1017.00
ZR28K5PFV800	R22	28,900	208-230/1/60	15.7	45 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	60	867.60
ZR28K5TF5800	R22	28,500	200-230/3/60	11.1	—	7.5 x 7.5	15.86	3/4 S	1/2 S	60	1033.20
ZR28K5TFD800	R22	28,500	460/3/60	5.7	—	7.5 x 7.5	15.86	3/4 S	1/2 S	68	1033.20
ZR28K5EPFV800	R407C, R22	28,400	208-230/1/60	15.7	45 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	60	881.10
ZR28K5EPFJ800	R407C, R22	28,400	265/1/60	13.9	45 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	60	940.50
ZR28K5ETF5800	R407C, R22	28,400	200-230/3/60	11.1	—	7.5 x 7.5	15.86	3/4 S	1/2 S	60	1050.30
ZR28K5ETF800	R407C, R22	28,400	460/3/60	5.7	—	7.5 x 7.5	15.86	3/4 S	1/2 S	68	1050.30
ZR32K5PFV800	R22	32,600	208-230/1/60	17.1	50 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	63	900.90
ZR32K5TF5800	R22	32,600	200-230/3/60	12.0	—	7.5 x 7.5	15.86	3/4 S	1/2 S	58	1079.10
ZR32K5TFD800	R22	32,600	460/3/60	6.4	—	7.5 x 7.5	15.86	3/4 S	1/2 S	58	1079.10
ZR32K5EPFV800	R407C, R22	32,600	208-230/1/60	17.1	50 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	63	900.00
ZR32K5EPFJ800	R407C, R22	32,600	265/1/60	14.3	45 x 370	7.5 x 7.5	15.86	3/4 S	1/2 S	63	960.30
ZR32K5ETF5800	R407C, R22	32,600	200-230/3/60	12.0	—	7.5 x 7.5	15.86	3/4 S	1/2 S	58	1071.90
ZR32K5ETF800	R407C, R22	32,600	460/3/60	6.4	—	7.5 x 7.5	15.86	3/4 S	1/2 S	58	1071.90
ZR38K5PFV800	R22	38,000	208-230/1/60	21.4	55 x 370	7.5 x 7.5	16.25	3/4 S	1/2 S	63	972.00
ZR38K5TF5800	R22	38,000	200-230/3/60	13.6	—	7.5 x 7.5	16.25	3/4 S	1/2 S	63	1138.50
ZR38K5TFD800	R22	38,000	460/3/60	6.4	—	7.5 x 7.5	16.25	3/4 S	1/2 S	70	1138.50
ZR38K5EPFV800	R407C, R22	38,000	208-230/1/60	21.4	55 x 370	7.5 x 7.5	16.25	3/4 S	1/2 S	63	988.20
ZR38K5EPFJ800	R407C, R22	38,000	265/1/60	16.4	60 x 370	7.5 x 7.5	16.25	3/4 S	1/2 S	63	1054.80
ZR38K5ETF5800	R407C, R22	38,000	200-230/3/60	13.6	—	7.5 x 7.5	16.25	3/4 S	1/2 S	63	1130.40
ZR38K5ETF800	R407C, R22	38,000	460/3/60	6.4	—	7.5 x 7.5	16.25	3/4 S	1/2 S	70	1130.40
ZR42K5PFV800	R22	42,200	208-230/1/60	22.1	55 x 370	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1014.30
ZR42K5TF5800	R22	42,200	200-230/3/60	14.3	—	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1162.80
ZR42K5TFD800	R22	42,200	460/3/60	6.4	—	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1162.80
ZR42K5EPFV800	R407C, R22	42,200	208-230/1/60	22.1	55 x 370	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1025.10
ZR42K5EPFJ800	R407C, R22	42,200	265/1/60	19.3	60 x 440	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1094.40
ZR42K5ETF5800	R407C, R22	42,200	200-230/3/60	14.3	—	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1172.70
ZR42K5ETF800	R407C, R22	42,200	460/3/60	6.4	—	7.5 x 7.5	16.25	3/4 S	1/2 S	72	1172.70
ZR47K3PFV935	R22	48,200	208-230/1/60	21.4	60 x 440	7.5 x 7.5	16.95	7/8 S	1/2 S	80	1106.10
ZR47K3TF5935	R22	47,500	200-230/3/60	16.4	—	7.5 x 7.5	16.95	7/8 S	1/2 S	80	1298.70
ZR48K5PFV800	R22	48,200	208-230/1/60	24.3	60 x 440	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1160.10
ZR48K5TF5800	R22	48,200	200-230/3/60	17.1	—	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1328.40
ZR48K5TFD800	R22	48,200	460/3/60	7.9	—	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1328.40

Prices above are list prices. Please call us for our discount pricing!

Continued on next page

SCROLL COMPRESSOR

ZR SERIES, 1 1/2 TO 25 HP (Cont'd.)



Part No.	Refrig	Capacity		RLA (Amps)	Run Capacitor (µf x Voltage)	Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
		(BTUH)	Voltage					Suction	Discharge		
ZR48K5EPFV800	R407C, R22	48,200	208-230/1/60	24.3	60 x 440	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1177.20
ZR48K5ETF5800	R407C, R22	48,200	200-230/3/60	17.1	—	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1346.40
ZR48K5ETF800	R407C, R22	48,200	460/3/60	7.9	—	7.5 x 7.5	16.95	7/8 S	1/2 S	72	1346.40
ZR54K5PFV800	R22	53,500	208-230/1/60	28.2	80 x 370	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1221.30
ZR54K5TF5800	R22	53,500	200-230/3/60	17.1	—	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1396.80
ZR54K5TFD800	R22	53,500	460/3/60	7.9	—	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1396.80
ZR54K5EPFV800	R407C, R22	53,500	208-230/1/60	28.2	80 x 370	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1236.60
ZR54K5ETF5800	R407C, R22	53,500	200-230/3/60	17.1	—	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1414.80
ZR54K5ETF800	R407C, R22	53,500	460/3/60	7.9	—	7.5 x 7.5	17.75	7/8 S	1/2 S	73	1414.80
ZR57K3PFV930	R22	58,000	208-230/1/60	32.1	80 x 370	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1314.00
ZR57K3TF5930	R22	58,500	200-230/3/60	19.3	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1416.60
ZR57K3TFD930	R22	58,500	460/3/60	10.0	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1416.60
ZR61K3PFV930	R22	62,000	208-230/1/60	32.1	80 x 370	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1384.20
ZR61K3TF5930	R22	62,000	200-230/3/60	19.3	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1492.20
ZR61K3TFD930	R22	62,000	460/3/60	10.0	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1492.20
ZR61K3EPFV930	R407C, R22	62,000	208-230/1/60	32.1	80 x 370	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1421.10
ZR61K3ETF930	R407C, R22	62,000	460/3/60	10.0	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1532.70
ZR67KWPFV930	R22	70,000	200-230/1/60	20.7	80 x 440	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1290.60
ZR68KCTF5930	R22	70,000	200-230/3/60	20.7	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1427.40
ZR68KCTFD930	R22	70,000	460/3/60	10.0	—	7.5 x 7.5	17.75	7/8 S	1/2 S	87	1427.40
ZR72KCTF5950	R22	73,500	200-230/3/60	20.7	—	7.5 x 7.5	17.70	7/8 S	1/2 S	87	1512.90
ZR72KCTF5965	R22	73,500	200-230/3/60	20.7	—	7.5 x 7.5	17.70	1 1/4 RL	1 RL	87	1547.10
ZR72KCTFD965	R22	73,500	460/3/60	10.0	—	7.5 x 7.5	17.75	1 1/4 RL	1 RL	87	1547.10
ZR72KCTFD950	R22	73,500	460/3/60	10	—	7.5 x 7.5	17.75	7/8 S	1/2 S	85	1512.90
ZR81KCTF5950	R22	82,000	200-230/3/60	25	—	7.5 x 7.5	17.95	7/8 S	3/4 S	86	1845.00
ZR81KCTFD950	R22	82,000	460/3/60	12.1	—	7.5 x 7.5	17.95	7/8 S	3/4 S	86	1845.00
ZR84KCTF5950	R22	84,000	200-230/3/60	28.6	—	7.5 x 7.5	18.80	1 1/8 S	7/8 S	127	2698.20
ZR84KCTFD950	R22	84,000	460/3/60	14.2	—	7.5 x 7.5	18.80	2 1/8 S	7/8 S	127	2698.20
ZR90K3TWC961	R22	88,800	208-230/3/60	33.6	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	215	3795.30
ZR90K3TWD961	R22	88,800	460/3/60	15.4	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	215	3795.30
ZR90K3ETWC961	R407C, R22	86,500	208-230/3/60	33.6	—	8.7 x 8.7	21.40	1 3/4 RL	1 1/4 RL	215	3888.00
ZR90K3ETWD961	R407C, R22	86,500	460/3/60	15.4	—	8.7 x 8.7	21.40	1 3/4 RL	1 1/4 RL	215	3888.00
ZR94KCTF5950	R22	95,600	200-230/3/60	32.1	—	7.5 x 7.5	18.80	1 1/8 S	7/8 S	150	2801.70
ZR94KCTFD950	R22	95,600	460/3/60	16.4	—	7.5 x 7.5	18.80	1 1/8 S	7/8 S	150	2801.70
ZR94KCTF5965	R22	95,600	200-230/3/60	32.1	—	7.5 x 7.5	18.80	1 3/4 RL	1 1/4 RL	150	2853.90
ZR94KCTFD965	R22	95,600	460/3/60	16.4	—	7.5 x 7.5	18.80	1 3/4 RL	1 1/4 RL	150	2853.90
ZR108KCTF5950	R22	108,000	200-230/3/60	33.6	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3002.40
ZR108KCTF5965	R22	108,000	200-230/3/60	33.6	—	7.5 x 7.5	21.50	1 3/4 RL	1 1/4 RL	150	3066.30
ZR108KCTFD950	R22	108,000	460/3/60	17.3	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3002.40
ZR108KCTFD965	R22	108,000	460/3/60	17.3	—	7.5 x 7.5	21.50	1 3/4 RL	1 1/4 RL	150	3066.30
ZR11M3TWC961	R22	108,000	208-230/3/60	33.3	—	8.7 x 8.7	21.20	1 3/4 RL	1 1/4 RL	221	4023.90
ZR11M3TWD961	R22	108,000	460/3/60	17.0	—	8.7 x 8.7	21.20	1 3/4 RL	1 1/4 RL	221	4023.90
ZR11M3ETWC961	R407C, R22	105,000	208-230/3/60	38.2	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	212	4117.50
ZR11M3ETWD961	R407C, R22	105,000	460/3/60	18.6	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	212	4117.50
ZR125KCTF5950	R22	125,000	200-230/3/60	42.0	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3201.30
ZR125KCTF5965	R22	125,000	200-230/3/60	42.0	—	7.5 x 7.5	21.50	1 3/4 RL	1 1/4 RL	150	3265.20
ZR125KCTFD950	R22	125,000	460/3/60	19.2	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3201.30
ZR125KCTFD965	R22	125,000	460/3/60	19.2	—	7.5 x 7.5	21.50	1 3/4 RL	1 1/4 RL	150	3265.20
ZR125KCETF5950	R407C, R22	125,000	200-230/3/60	41.4	—	7.5 x 7.5	21.00	1 3/8 S	7/8 S	135	3264.30
ZR125KCETF950	R407C, R22	125,000	460/3/60	19.2	—	7.5 x 7.5	21.00	1 3/8 S	7/8 S	135	3264.30
ZR12M3TWC961	R22	125,000	208-230/3/60	39.5	—	8.7 x 8.7	21.20	1 3/4 RL	1 1/4 RL	221	4187.70
ZR12M3TWD961	R22	125,000	460/3/60	18.8	—	8.7 x 8.7	21.20	1 3/4 RL	1 1/4 RL	221	3866.40
ZR12M3ETWC961	R407C, R22	122,000	208-230/3/60	41.1	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	221	4281.30
ZR12M3ETWD961	R407C, R22	122,000	460/3/60	22.1	—	8.7 x 8.7	21.17	1 3/4 RL	1 1/4 RL	221	4281.30
ZR144KCTF5950	R22	144,000	200-230/3/60	47.1	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3409.20
ZR144KCTFD950	R22	144,000	460/3/60	19.6	—	7.5 x 7.5	21.50	1 3/8 S	7/8 S	150	3409.20
ZR160KCETW5950	R407C, R22	154,000	200-230/3/60	55.0	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	3827.70
ZR160KCETW5965	R407C, R22	154,000	200-230/3/60	55.0	—	7.5 x 7.5	21.47	1 3/4 RL	1 1/4 RL	200	3895.20
ZR160KCETWD950	R407C, R22	154,000	460/3/60	25.7	—	7.5 x 7.5	21.47	1 3/8 S	7/8 S	200	3827.70

Prices above are list prices. Please call us for our discount pricing!

Continued on next page

ZR SERIES, 1 1/2 TO 25 HP (Cont'd.)



Part No.	Refrig	Capacity		RLA (Amps)	Run Capacitor (µf x Voltage)	Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
		(BTUH)	Voltage					Suction	Discharge		
ZR160KCETWD965	R407C, R22	154,000	460/3/60	25.7	—	7.5 x 7.5	21.47	1 3/4 RL	1 1/4 RL	200	3895.20
ZR160KCTW5950	R22	154,000	200-230/3/60	55.0	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	3758.40
ZR160KCTW5965	R22	154,000	200-230/3/60	55.0	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	3825.90
ZR160KCTWD950	R22	154,000	460/3/60	25.7	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	3758.40
ZR160KCTWD965	R22	154,000	460/3/60	25.7	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	3825.90
ZR190KCETW5950	R407C, R22	181,000	200-230/3/60	60.0	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	4185.00
ZR190KCETW5965	R407C, R22	181,000	200-230/3/60	60.0	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	4252.50
ZR190KCETWD950	R407C, R22	181,000	460/3/60	31.4	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	4185.00
ZR190KCETWD965	R407C, R22	181,000	460/3/60	31.4	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	4252.50
ZR190KCTW5950	R22	181,000	200-230/3/60	60.0	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	4115.70
ZR190KCTW5965	R22	181,000	200-230/3/60	60.0	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	4183.20
ZR190KCTWD950	R22	181,000	460/3/60	31.4	—	7.5 x 7.5	22.00	1 3/8 S	7/8 S	200	4115.70
ZR190KCTWD965	R22	181,000	460/3/60	31.4	—	7.5 x 7.5	22.00	1 3/4 RL	1 1/4 RL	200	4183.20
ZR250KCETW5951	R407C, R22	240,000	200-230/3/60	81.4	—	10.5 x 10.5	28.60	1 5/8 S	1 3/8 S	320	7451.10
ZR250KCETW5965	R407C, R22	240,000	200-230/3/60	81.4	—	10.5 x 10.5	28.60	2 1/4 RL	1 3/4 RL	308	7567.26
ZR250KCETWD951	R407C, R22	240,000	460/3/60	37.9	—	10.5 x 10.5	28.60	1 5/8 S	1 3/8 S	320	7451.10
ZR250KCETWD965	R407C, R22	240,000	460/3/60	37.9	—	10.5 x 10.5	28.60	2 1/4 RL	1 3/4 RL	308	7567.20
ZR250KCTW5951	R22	250,000	200-230/3/60	81.4	—	10.5 x 10.5	28.60	1 5/8 S	1 3/8 S	320	7373.30
ZR250KCTW5965	R22	250,000	200-230/3/60	81.4	—	10.5 x 10.5	28.60	2 1/4 RL	1 3/4 RL	320	7489.80
ZR250KCTWD951	R22	250,000	460/3/60	37.9	—	10.5 x 10.5	28.60	1 5/8 S	1 3/8 S	308	7373.70
ZR250KCTWD965	R22	250,000	460/3/60	40.5	—	10.5 x 10.5	29.00	2 1/4 RL	1 3/4 RL	308	7489.80
ZR300KCETW5951	R407C, R22	293,000	200-230/3/60	100	—	10.5 x 10.5	28.50	2 1/8 S	1 3/8 S	430	8894.70
ZR300KCETW5965	R407C, R22	293,000	200-230/3/60	100	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	406	9012.15
ZR300KCETWD951	R407C, R22	293,000	460/3/60	48.6	—	10.5 x 10.5	28.50	2 1/8 S	1 3/8 S	430	8894.70
ZR300KCETWD965	R407C, R22	293,000	460/3/60	48.6	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	406	9011.70
ZR300KCTW5951	R22	296,000	200-230/3/60	87.9	—	10.5 x 10.5	28.50	2 1/8 S	1 3/8 S	430	8788.67
ZR300KCTW5965	R22	296,000	200-230/3/60	87.9	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	406	8906.52
ZR300KCTWD951	R22	296,000	460/3/60	42.9	—	10.5 x 10.5	28.50	2 1/8 S	1 3/8 S	406	8788.50
ZR300KCTWD965	R22	296,000	460/3/60	42.9	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	406	8906.40
ZR380KCETWC965	R407C, R22	374,000	208-230/3/60	121.4	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	440	10648.80
ZR380KCETWD965	R407C, R22	374,000	460/3/60	59.3	—	10.5 x 10.5	28.50	2 1/4 RL	1 3/4 RL	440	10648.80



ZP SERIES, 1 1/2 TO 15 HP, R410A

- Suitable for air conditioning applications.
- **Capacitor** required, not provided
- Capacity rated R410A, 45°F evaporator, 130°F condensing
- **(Bold) Connection** = Rotolock valve, adapter required (961 suffix)



Part No.	Capacity		RLA (Amps)	Run Capacitor (µf x Voltage)	Quad Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
	(BTUH)	Voltage					Suction	Discharge		
ZP14K5EPFV830	14650	208-230/1/60	10	30 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	53	946.80
ZP16K5EPFV830	15500	208-230/1/60	10	30 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	53	946.80
ZP16K5EPFJ830	15500	265/1/60	7.9	35 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	53	1011.60
ZP20K5EPFV830	20000	208-230/1/60	15.0	35 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	947.70
ZP20K5EPFJ830	20000	265/1/60	10.0	40 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1012.50
ZP21K5EPFV830	21300	208-230/1/60	14.3	40 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	54	951.30
ZP21K5EPFJ830	21300	265/1/60	10.7	40 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	54	1016.10
ZP21K5ETF5830	21300	200-230/3/60	8.6	—	7.5 x 7.5	16.02	3/4 S	1/2 S	54	⚡
ZP21K5ETFD830	21300	460/3/60	4	—	7.5 x 7.5	16.02	3/4 S	1/2 S	54	1135.80
ZP25K5EPFV830	25200	208-230/1/60	15.7	40 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	978.30
ZP25K5EPFJ830	25200	265/1/60	12.5	40 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1044.90
ZP25K5ETF5830	25200	200-230/3/60	9.9	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1169.10
ZP25K5ETFD830	25200	460/3/60	4.6	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1169.10
ZP28K5EPFV830	27900	208-230/1/60	17.9	45 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1011.60
ZP28K5ETF5830	27900	200-230/3/60	11.1	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1207.80
ZP28K5ETFD830	27900	460/3/60	5.3	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1207.80
ZP29K5EPFV830	29000	208-230/1/60	15.7	45 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1020.60
ZP29K5EPFJ830	29000	265/1/60	13.6	60 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1089.90
ZP29K5ETF5830	29000	200-230/3/60	10	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1218.60

Prices above are list prices. Please call us for our discount pricing!

Continued on next page

SCROLL COMPRESSOR

ZP SERIES, 1 1/2 TO 15 HP, R410A (Cont'd.)



Part No.	Capacity		RLA (Amps)	Run Capacitor (µf x Voltage)	Quad Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
	(BTUH)	Voltage					Suction	Discharge		
ZP29K5ETFD830	29000	460/3/60	6.3	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1218.60
ZP31K5EPFV830	31100	208-230/1/60	18.6	45 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1033.20
ZP31K5EPFJ830	31100	265/1/60	15	60 x 370	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1103.40
ZP31K5ETF5830	31200	200-230/3/60	11.6	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1233.90
ZP31K5ETFD830	31200	460/3/60	6.4	—	7.5 x 7.5	16.02	3/4 S	1/2 S	55	1233.90
ZP34K5EPFV830	34500	208-230/1/60	20	45 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	75	1089.90
ZP34K5ETF5830	34600	200-230/3/60	14.7	—	7.5 x 7.5	17.17	7/8 S	1/2 S	75	1249.20
ZP34K5ETFD830	34600	460/3/60	6.6	—	7.5 x 7.5	17.17	7/8 S	1/2 S	75	1249.20
ZP36K5EPFV830	36000	208-230/1/60	20	45 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	76	1107.00
ZP36K5EPFJ830	36000	265/1/60	17.9	60 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	76	1182.60
ZP36K5ETF5830	36000	200-230/3/60	15.1	—	7.5 x 7.5	17.17	7/8 S	1/2 S	76	1268.10
ZP36K5ETFD830	36000	460/3/60	6.6	—	7.5 x 7.5	17.17	7/8 S	1/2 S	76	1268.10
ZP38K5EPFV830	37500	208-230/1/60	22.1	45 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1155.60
ZP38K5ETF5830	38000	200-230/3/60	15.1	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1323.00
ZP38K5ETFD830	38100	460/3/60	6.8	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1323.00
ZP39K5EPFV830	39000	208-230/1/60	22.1	45 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1163.70
ZP39K5ETF5830	39000	200-230/3/60	14.6	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1332.90
ZP39K5ETFD830	39000	460/3/60	6.8	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1332.90
ZP42K5EPFV830	42000	208-230/1/60	24.3	70 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1199.70
ZP42K5EPFJ830	42000	265/1/60	18.1	80 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1281.60
ZP42K5ETF5830	42200	200-230/3/60	15.3	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1374.30
ZP42K5ETFD830	41900	460/3/60	6.9	—	7.5 x 7.5	17.17	7/8 S	1/2 S	79	1374.30
ZP44K5EPFV830	44400	200-230/1/60	23.9	70 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	75	1254.60
ZP44K5EPFJ830	44,400	265/1/60	20.9	80 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	75	1339.93
ZP44K5ETF5830	44500	200-230/3/60	16.1	—	7.5 x 7.5	17.17	7/8 S	1/2 S	70	1437.30
ZP44K5ETFD830	44500	460/3/60	7.1	—	7.5 x 7.5	17.17	7/8 S	1/2 S	70	1437.30
ZP49K5EPFV830	49400	208-230/1/60	27.9	70 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1395.90
ZP49K5EPFJ830	49200	265/1/60	23.8	70 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1491.30
ZP49K5ETF5830	49700	200-230/3/60	17.7	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1599.30
ZP49K5ETFD830	50000	460/3/60	7.9	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1599.30
ZP51K5EPFV830	51000	208-230/1/60	29.4	70 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1432.80
ZP51K5EPFJ830	51200	265/1/60	22.1	80 x 440	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1530.00
ZP51K5ETF5830	51500	200-230/3/60	17.8	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1640.70
ZP51K5ETFD830	51500	460/3/60	8.6	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1640.70
ZP54K5EPFV830	54000	208-230/1/60	29.3	80 x 370	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1454.40
ZP54K5EPFJ830	54000	265/1/60	22.1	80 x 440	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1553.40
ZP54K5ETF5830	54300	200-230/3/60	17.4	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1666.80
ZP54K5ETFD830	54300	460/3/60	8.6	—	7.5 x 7.5	17.17	7/8 S	1/2 S	81	1666.80
ZP57K5EPFV830	57000	208-230/1/60	31.6	80 x 370	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1492.20
ZP57K5ETF5830	57500	200-230/3/60	21.4	—	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1710.00
ZP57K5ETFD830	57500	460/3/60	9.7	—	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1710.00
ZP61K5EPFV830	61500	208-230/1/60	34.3	80 x 370	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1594.01
ZP61K5ETF5830	61500	200-230/3/60	21.9	—	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1826.14
ZP61K5ETFD830	61500	460/3/60	9.1	—	7.5 x 7.5	17.59	7/8 S	1/2 S	81	1826.14
ZP72KCETF5950	72,000	200-230/3/60	25.9	—	7.5 x 7.5	18.16	7/8 S	1/2 S	97	1845.00
ZP72KCETFD950	72,000	460/3/60	12.5	—	7.5 x 7.5	18.16	7/8 S	1/2 S	97	1845.45
ZP83KCETF5950	83,000	200-230/3/60	27.9	—	7.5 x 7.5	18.16	7/8 S	1/2 S	97	2120.40
ZP83KCETFD950	83,000	460/3/60	13.6	—	7.5 x 7.5	18.16	7/8 S	1/2 S	97	2120.40
ZP90KCETF5950	90,500	200-230/3/60	32.9	—	7.5 x 7.5	19.50	1 1/8 S	7/8 S	132	2795.40
ZP90KCETFD950	90,500	460/3/60	16.4	—	7.5 x 7.5	19.50	1 1/8 S	7/8 S	132	2795.40
ZP103KCETF5950	105,000	200-230/3/60	33.6	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	132	3026.70
ZP103KCETFD950	105,000	460/3/60	18.6	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	132	3026.70
ZP120KCETF5950	121,000	200-230/3/60	37.1	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	135	3227.40
ZP120KCETFD950	121,000	460/3/60	20.0	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	135	3227.40
ZP137KCETF5950	137,000	200-230/3/60	53.6	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	145	3451.50
ZP137KCETFD950	137,000	460/3/60	20.7	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	145	3451.50

Prices above are list prices. Please call us for our discount pricing!

Continued on next page

ZP SERIES, 1 1/2 TO 15 HP R410A (Cont'd.)



Part No.	Capacity (BTUH)	Voltage	RLA (Amps)	Run Capacitor (µf x Voltage)	Quad Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
							Suction	Discharge		
ZP154KCETW5950	155,000	200-230/3/60	57.1	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	146	3755.70
ZP154KCETWD950	155,000	460/3/60	25.7	—	7.5 x 7.5	21.75	1 3/8 S	7/8 S	146	3755.70
ZP182KCETW5950	183,000	208-230/3/60	62.1	—	7.5 x 7.5	21.71	1 3/8 S	7/8 S	146	4111.20
ZP182KCETWD950	183,000	460/3/60	30.0	—	7.5 x 7.5	21.71	1 3/8 S	7/8 S	146	4111.20
ZP235KCETWC951	235,000	208-230/3/60	82.4	—	10.5 x 10.5	29.0	1 5/8 S	1 3/8 S	324	7221.60
ZP235KCETWD951	235,000	460/3/60	33.9	—	10.5 x 10.5	29.0	1 5/8 S	1 3/8 S	324	7221.60
ZP385KCETWC965	385,000	208-230/3/60	122.1	—	10.5 x 10.5	28.9	2 1/4 RL	1 3/4 RL	390	9540.90
ZP385KCETWD965	385,000	460/3/60	60.7	—	10.5 x 10.5	28.9	2 1/4 RL	1 3/4 RL	390	9770.40



DIGITAL R410A

Digital scroll compressors are variable capacity compressors that can modulate down to 10% of full load. Digital scrolls are suitable for a variety of applications where a variable capacity compressor is useful, such as VAV applications, dedicated outside air units, units that typically used

hot gas bypass for capacity control, and applications that require accurate control of temperature and humidity. Other applications include multiple compressor systems where modulation is required over the entire operating range of the system and in applications where compressor starting and stopping is unacceptable. Use of the unloading feature requires a normally closed solenoid valve to disengage the scroll elements.



Part No.	Capacity (BTUH)	Voltage	RLA (Amps)	Height (In.)	Connections (In.)		Mount (In.) L x W	Ship Wgt. (Lbs.)	Price
					Suction	Discharge			
ZPD34K5EPFV830	34,500	208-230/1/60	20.6	18.41	3/4 S	1/2 S	7.5 x 7.5	72	1765.80
ZPD34K5EPFJ830	34,600	265/1/60	17.9	18.41	7/8 S	1/2 S	7.5 x 7.5	72	1886.40
ZPD34K5ETF5830	34,600	200-230/3/60	13.0	18.41	7/8 S	1/2 S	7.5 x 7.5	72	2023.20
ZPD34K5ETFD830	34,600	460/3/60	6.9	18.41	7/8 S	1/2 S	7.5 x 7.5	72	2023.20
ZPD42K5EPFV830	42,000	208-230/1/60	22.5	19.14	7/8 S	1/2 S	7.5 x 7.5	75	1943.10
ZPD42K5ETFD830	42,600	460/3/60	8.6	18.41	3/4 S	1/2 S	7.5 x 7.5	75	2226.60
ZPD42K5ETF5830	43,000	200-230/3/60	17.9	18.41	3/4 S	1/2 S	7.5 x 7.5	75	2226.60
ZPD51K5EPFV830	51,500	208-230/1/60	28.6	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2320.20
ZPD51K5ETF5830	51,400	200-230/3/60	20.0	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2658.60
ZPD51K5ETFD830	51,000	460/3/60	8.6	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2658.60
ZPD54K5EPFV830	54,000	208-230/1/60	28.6	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2356.20
ZPD54K5ETF5830	54,600	200-230/3/60	18.8	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2699.10
ZPD54K5ETFD830	54,500	460/3/60	9.0	19.14	7/8 S	1/2 S	7.5 x 7.5	80	2699.10
ZPD61KCETF5950	63,000	200-230/3/60	22.7	19.71	7/8 S	1/2 S	7.5 x 7.5	93	2677.50
ZPD61KCETFD950	62,000	460/3/60	10.9	19.71	7/8 S	1/2 S	7.5 x 7.5	93	2677.50
ZPD72KCETF5950	72,000	200-230/3/60	25.9	19.71	7/8 S	1/2 S	7.5 x 7.5	93	2891.70
ZPD72KCETFD950	71,500	460/3/60	12.5	19.71	7/8 S	1/2 S	7.5 x 7.5	93	2891.70
ZPD83KCETF5950	82,500	200-230/3/60	26.8	19.71	7/8 S	1/2 S	7.5 x 7.5	93	3323.70
ZPD83KCETFD950	83,000	460/3/60	14.1	19.71	7/8 S	1/2 S	7.5 x 7.5	93	3323.70
ZPD91KCETF5950	90,100	200-230/3/60	30.7	19.71	7/8 S	3/4 S	7.5 x 7.5	95	3642.30
ZPD91KCETFD950	90,100	460/3/60	14.3	19.71	7/8 S	3/4 S	7.5 x 7.5	95	3642.30
ZPD103KCETF5950	105,000	200-230/3/60	33.6	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	4807.80
ZPD103KCETFD950	105,000	460/3/60	18.6	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	4807.39
ZPD120KCETF5950	123,000	200-230/3/60	37.1	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	5126.40
ZPD120KCETFD950	123,000	460/3/60	20.0	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	5126.40
ZPD137KCETF5950	137,500	200-230/3/60	53.6	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	5482.80
ZPD137KCETFD950	137,500	460/3/60	20.7	21.75	1 3/8 S	7/8 S	7.5 x 7.5	140	5482.80
ZPD154KCETW5950	155,000	200-230/3/60	57.1	23.03	1 3/8 S	7/8 S	7.5 x 7.5	152	5697.00
ZPD154KCETWD950	155,000	460/3/60	25.7	23.03	1 3/8 S	7/8 S	7.5 x 7.5	152	5697.00
ZPD182KCETW5950	183,000	200-230/3/60	62.1	22.46	1 3/8 S	7/8 S	7.5 x 7.5	152	6236.10
ZPD182KCETWD950	183,000	460/3/60	30.0	22.46	1 3/8 S	7/8 S	7.5 x 7.5	152	6236.10

Prices above are list prices. Please call us for our discount pricing!

SCROLL COMPRESSOR



TANDEM R22 R407C

Tandem scroll compressor systems offer higher capacities, unloading efficiencies and the reliability of the Copeland scroll technology.

- Rated load amps at full capacity (estimated)
- Capacity rated +45°F SST, 130°F Condensing, R22
- K*E models with POE oil for use with R407C



Part No.	Capacity (BTUH)		Voltage	Oil	RLA (Amps)	Overall Dimensions (In.)			Connections (In.)		Mount (In.)	Ship Wgt. (Lbs.)	Price
	Full/Half					L	W	H	Suction	Discharge	L x W		
ZRT90K3PFV930	90,500/45,500		208-230/1/60	MIN	—	24.33	11.37	18.34	1 1/8 S	3/4 S	21.5 x 7.5	136	2945.70
ZRT96K3PFV930	98,500/49,400		208-230/1/60	MIN	—	24.33	11.37	17.99	1 1/8 S	3/4 S	21.5 x 7.5	136	3234.60
ZRT96KCTF5930	96,800/46,000		200-230/3/60	MIN	—	24.33	11.37	17.99	1 1/8 S	3/4 S	21.5 x 7.5	136	3365.10
ZRT96KCTFD930	96,800/48,600		460/3/60	MIN	—	24.33	11.37	17.99	1 1/8 S	3/4 S	21.5 x 7.5	136	3650.40
ZRT96K3ETF5930	92,500/46,800		200-230/3/60	POE	—	24.33	11.37	17.99	1 1/8 S	3/4 S	21.5 x 7.5	136	3785.03
ZRT96K3ETFD930	97,000/49,300		460/3/60	POE	—	24.33	11.37	17.99	1 1/8 S	3/4 S	21.5 x 7.5	136	3785.03
ZRT108K3PFV950	109,000/54,300		208-230/1/60	MIN	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	200	3254.40
ZRT108K3TF5950	108,000/53,900		200-230/3/60	MIN	38.6	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	200	3510.00
ZRT108K3TFD950	108,000/53,900		460/3/60	MIN	15.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	200	3510.00
ZRT114K3PFV950	116,000/57,600		208-230/1/60	MIN	64.2	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	224	3249.74
ZRT114K3TF5950	115,000/57,400		200-230/3/60	MIN	38.6	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	224	3504.60
ZRT114K3TFD950	115,000/57,400		460/3/60	MIN	20.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	224	3504.60
ZRT122K3PFV950	121,000/60,600		208-230/1/60	MIN	64.2	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	225	3395.70
ZRT122K3TF5950	121,000/60,600		200-230/3/60	MIN	30.8	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	192	3662.10
ZRT122K3TFD950	121,000/60,600		460/3/60	MIN	15.4	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	192	3662.10
ZRT136KCTF5950	137,000/68,500		200-230/3/60	MIN	41.4	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3545.10
ZRT136KCTFD950	137,000/68,500		460/3/60	MIN	20.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3545.10
ZRT136KCTF5950	132,000/65,500		200-230/3/60	POE	41.4	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3630.60
ZRT136KCTFD950	132,000/65,500		460/3/60	POE	20.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3630.60
ZRT136KCTF5930	132,000/65,500		200-230/3/60	POE	41.4	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3630.60
ZRT136KCTFD930	132,000/65,500		460/3/60	POE	20.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3630.60
ZRT144KCTF5950	144,000/72,700		200-230/3/60	MIN	36.6	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	202	3752.10
ZRT144KCTFD950	144,000/72,700		460/3/60	MIN	18.3	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	202	3752.10
ZRT144KCTF5950	137,000/68,500		200-230/3/60	POE	41.4	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3836.98
ZRT144KCTFD950	137,000/68,500		460/3/60	POE	20.0	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	3836.98
ZRT162KCTF5950	163,000/81,500		200-230/3/60	MIN	50.0	24.65	12.50	19.02	1 1/8 S	1 1/8 S	21.5 x 7.5	205	4231.80
ZRT162KCTFD950	163,000/81,500		460/3/60	MIN	24.2	24.65	12.50	19.02	1 1/8 S	1 1/8 S	21.5 x 7.5	205	4231.80
ZRT162KCTF5950	154,000/77,500		200-230/3/60	POE	50.0	24.65	12.50	19.02	1 1/8 S	1 1/8 S	21.5 x 7.5	205	4317.13
ZRT162KCTFD950	154,000/77,500		460/3/60	POE	24.2	24.65	12.50	19.02	1 1/8 S	1 1/8 S	21.5 x 7.5	205	4317.13
ZRT168KCTF5950	171,000/—		200-230/3/60	MIN	—	25.00	12.30	19.50	1 5/8 S	1 3/8 S	19.75 x 10.00	285	7440.30
ZRT168KCTFD950	171,000/—		460/3/60	MIN	—	25.00	12.30	19.50	1 5/8 S	1 3/8 S	19.75 x 10.00	280	7440.30
ZRT188KCTF5950	189,000/94,600		200-230/3/60	MIN	50.0	35.08	17.75	22.40	1 5/8 S	1 1/8 S	14.67 x 8.66	500	7645.50
ZRT188KCTFD950	189,000/94,600		460/3/60	MIN	25.0	35.08	17.75	22.40	1 5/8 S	1 1/8 S	14.67 x 8.66	500	7645.50
ZRT216KCTF5950	215,000/108,000		200-230/3/60	MIN	67.2	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.00	283	8110.80
ZRT216KCTFD950	215,000/108,000		460/3/60	MIN	34.6	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.00	283	8110.80
ZRT250KCTF5950	252,000/126,000		200-230/3/60	MIN	—	35.08	17.75	22.40	1 5/8 S	1 3/8 S	14.67 x 8.66	500	8547.30
ZRT250KCTFD950	252,000/126,000		460/3/60	MIN	—	35.08	17.75	22.40	1 5/8 S	1 3/8 S	14.67 x 8.66	500	8547.30
ZRT288KCTF5950	288,000/143,000		200-230/3/60	MIN	94.2	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.00	289	9003.60
ZRT288KCTFD950	288,000/143,000		460/3/60	MIN	47.2	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.00	289	9003.60
ZRT320KCTF5976	319,000/—		200-230/3/60	POE	—	25.00	12.3	23.5	1 5/8 S	1 3/8 S	19.75 x 10.00	300	9676.80
ZRT320KCTFD976	319,000/—		460/3/60	POE	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.00	300	9676.80
ZRT380KCTF5976	378,000/—		200-230/3/60	MIN	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.00	320	10269.90
ZRT380KCTFD976	378,000/—		460/3/60	MIN	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.00	320	10269.90
ZRT500KCTF5951	482,000/—		200-230/3/60	MIN	—	41.40	21.60	29.50	2 5/8 S	1 5/8 S	30.55 x 10.50	680	18628.24
ZRT500KCTFD951	482,000/—		460/3/60	MIN	—	41.40	21.60	29.76	2 5/8 S	1 5/8 S	30.55 x 10.47	560	18628.20
ZRT500KCTF5951	471,000/—		208-230/3/60	POE	162.8	41.40	21.60	29.50	2 5/8 S	1 5/8 S	30.55 x 10.47	659	18801.00
ZRT500KCTFD951	471,000/—		460/3/60	POE	81.0	41.40	21.60	29.50	2 5/8 S	1 5/8 S	30.55 x 10.47	659	18801.00
ZRT600KCTF5951	586,000/—		200-230/3/60	MIN	—	42.20	23.05	29.39	3 1/8 S	1 5/8 S	30.55 x 10.47	890	21561.68
ZRT600KCTFD951	586,000/—		460/3/60	MIN	85.8	42.20	23.05	29.39	3 1/8 S	1 5/8 S	30.55 x 10.47	864	21561.30
ZRT760KCTFD951	747,000/—		460/3/60	MIN	—	42.20	22.70	29.39	3 1/8 S	1 5/8 S	30.55 x 10.47	864	25170.30

Prices above are list prices. Please call us for our discount pricing!

TANDEM R410A



Part No.	Capacity (BTUH)		RLA (Amps)	Overall Dimensions (In.)			Connections (In.)		Mount (In.) L x W	Ship Wgt. (Lbs.)	Price
	Full/Half	Voltage		L	W	H	Suction	Discharge			
ZPT114KCETFD950	114,000/57,000	460/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	217	3995.10
ZPT122KCETF5950	121,000/60,500	208-230/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	217	3930.30
ZPT122KCETFD950	121,000/60,500	460/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	217	3930.30
ZPT144KCETF5950	141,000/70,500	208-230/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	205	4197.60
ZPT166KCETF5950	164,000/82,000	208-230/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	186	4737.60
ZPT166KCETFD950	164,000/82,000	460/3/60	—	24.65	11.69	18.80	1 1/8 S	3/4 S	21.5 x 7.5	186	4737.60
ZPT180KCETF5975	181,000/-	208-230/3/60	—	25.00	12.30	19.50	1 5/8 S	1 3/8 S	19.75 x 10.0	271	7863.30
ZPT180KCETFD975	181,000/-	460/3/60	—	25.00	12.30	19.50	1 5/8 S	1 3/8 S	19.75 x 10.0	270	7863.30
ZPT206KCETF5975	210,000/-	208-230/3/60	—	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.0	283	8379.00
ZPT206KCETFD975	210,000/-	460/3/60	—	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.0	283	8379.00
ZPT240KCETF5975	246,000/-	208-230/3/60	—	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.0	289	8825.40
ZPT274KCETF5975	270,000/-	208-230/3/60	—	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.0	289	9324.00
ZPT274KCETFD975	270,000/-	460/3/60	—	25.00	12.30	22.70	1 5/8 S	1 3/8 S	19.75 x 10.0	289	9324.00
ZPT308KCETWC975	307,000/-	208-230/3/60	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.0	286	9852.30
ZPT308KCETWD975	307,000/-	460/3/60	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.0	286	9891.90
ZPT364KCETWC975	361,000/-	208-230/3/60	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.0	292	10896.30
ZPT364KCETWD976	361,000/-	460/3/60	—	25.00	12.30	23.50	1 5/8 S	1 3/8 S	19.75 x 10.0	292	10647.00
ZPT470KCETWC951	464,000/-	208-230/3/60	—	41.40	21.60	29.50	2 5/8 S	1 5/8 S	30.58 x 10.5	697	17953.20
ZPT590KCETWC951	585,000/-	208-230/3/60	—	42.20	22.70	29.39	2 5/8 S	1 5/8 S	30.58 x 10.5	752	19917.90
ZPT770KCETWC951	765,000/-	208-230/3/60	—	42.20	22.70	29.39	2 5/8 S	1 5/8 S	30.58 x 10.5	826	22982.40
ZPT770KCETWD951	765,000/-	460/3/60	—	42.20	22.70	29.39	2 5/8 S	1 5/8 S	30.58 x 10.5	826	22982.40

TANDEM, DIGITAL R410A



Part No.	Capacity (BTUH)		RLA (Amps)	Overall Dimensions (In.)			Connections (In.)		Mount (In.) L x W	Ship Wgt. (Lbs.)	Price
	Full	Voltage		L	W	H	Suction	Discharge			
ZPDT12MCETF5950	123,500	200-230/3/60	—	24.62	11.56	20.82	1 1/8 S	3/4 S	21.5 x 7.5	217	⌘
ZPDT12MCETFD950	123,500	460/3/60	—	24.62	11.56	20.82	1 1/8 S	3/4 S	21.5 x 7.5	217	⌘
ZPDT14MCETF5950	143,000	200-230/3/60	—	24.62	11.56	20.82	1 1/8 S	3/4 S	21.5 x 7.5	217	⌘
ZPDT14MCETFD950	143,000	460/3/60	—	24.62	11.56	20.82	1 1/8 S	3/4 S	21.5 x 7.5	217	⌘
ZPDT18MCETF5950	179,000	200-230/3/60	—	24.62	12.12	20.82	1 1/8 S	1 1/8 S	21.5 x 7.5	217	⌘
ZPDT18MCETFD950	179,000	460/3/60	—	24.62	12.12	20.82	1 1/8 S	1 1/8 S	21.5 x 7.5	217	⌘
ZPDT21MCETF5950	209,000	200-230/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT21MCETFD950	209,000	460/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT24MCETF5950	246,000	200-230/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT24MCETFD950	246,000	460/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT27MCETF5950	270,000	200-230/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT27MCETFD950	270,000	460/3/60	—	29.37	15.87	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	300	⌘
ZPDT31MCETW5950	309,000	200-230/3/60	—	29.37	17.29	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	325	⌘
ZPDT31MCETWD950	309,000	460/3/60	—	29.37	17.29	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	325	⌘
ZPDT36MCETW5950	364,000	200-230/3/60	—	29.37	17.29	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	325	⌘
ZPDT36MCETWD950	364,000	460/3/60	—	29.37	17.29	23.00	1 5/8 S	1 3/8 S	19.75 x 10.0	325	⌘



COMFORT ALERT™

Diagnostic tool for systems with Copeland Scroll compressors. Entry level technician first diagnosis accuracy increased from 17% to 92%, experienced technician accuracy from 63% to 100%.

Detects following system and electrical problem conditions:

- Long Run Time
- System Pressure Trip
- Short Cycling
- Locked Rotor
- Open Circuit
- Open Run/Open Start Circuit
- Welded Contactor
- Low Supply Voltage



Part No.	Usage	Price
943001200	Heat Pump, Ultra Tech	190.48

Prices above are list prices. Please call us for our discount pricing!

SCROLL COMPRESSOR



RESIDENTIAL/LIGHT COMMERCIAL

Performer® scroll compressors are specially designed for commercial aAC applications. There is no contact between the scroll flanks in a Performer scroll compressor. The ultra-precise scroll profiles with controlled orbit, roll

and slide on an oil film without friction or wear. Floating tip seals ensure axial sealing with low friction losses. With these techniques, the Performer scroll compressor combines high energy efficiency with low sound and vibration characteristics. The 100% suction gas cooled and shielded motor, built-in motor protection, large oil reserve and

large internal free volume ensure high reliability and long lifetime.

- Optimized discharge assembly for low noise and higher efficiency.
- Precision balanced moving parts to reduce vibration.
- Shielded motor, 100% suction gas cooled.
- Carefully designed channel with low resistance to suction gas.
- Compact footprint and light weight.
- Ultra precise scroll profile. No contact between scroll flanks but sealing with oil film.
- Floating tip seals for perfect axial sealing, reducing friction losses.
- Large oil sump and large internal free volume.

HRM SERIES

- Rotolock connections require valve or adapter



Part No.	Capacity (BTUH)	Voltage	RLA (Amps)	Quad Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
						Suction	Discharge		
HRM032U1LP6	32312	208-230/1/60	16.7	7.5 x 7.5	15.53	3/4	1/2	63	891.00
HRM032U2LP6	31824	208-230/3/60	11.2	7.5 x 7.5	15.53	3/4	1/2	63	☞
HRM032U4LP6	31824	460/3/60	6.1	7.5 x 7.5	15.53	3/4	1/2	63	999.00
HRM034U1LP6	33500	208-230/1/60	16.7	7.5 x 7.5	15.53	3/4	1/2	63	908.00
HRM034U2LP6	33537	208-230/3/60	11.2	7.5 x 7.5	15.53	3/4	1/2	63	☞
HRM034U4LP6	33537	460/3/60	6.1	7.5 x 7.5	15.53	3/4	1/2	63	☞
HRM038U1LP6	38000	208-230/1/60	19.5	7.5 x 7.5	15.53	3/4	1/2	63	936.00
HRM038U2LP6	38000	208-230/3/60	12.2	7.5 x 7.5	15.53	3/4	1/2	63	1029.00
HRM038U4LP6	38012	460/3/60	6.4	7.5 x 7.5	15.53	3/4	1/2	63	☞
HRM040U1LP6	40000	208-230/1/60	21.0	7.5 x 7.5	15.53	3/4	1/2	63	954.00
HRM040U2LP6	40007	208-230/3/60	12.8	7.5 x 7.5	15.53	3/4	1/2	72	1050.00
HRM040U4LP6	40007	460/3/60	6.4	7.5 x 7.5	15.53	3/4	1/2	63	☞
HRM042U1LP6	42000	208-230/1/60	17.3	7.5 x 7.5	15.53	3/4	1/2	72	988.00
HRM042U2LP6	42000	208-230/3/60	14.1	7.5 x 7.5	15.53	3/4	1/2	72	1087.00
HRM042U4LP6	42034	460/3/60	7.1	7.5 x 7.5	15.53	3/4	1/2	72	☞
HRM047U1LP6	47500	208-230/1/60	24.4	7.5 x 7.5	16.53	7/8	1/2	72	1036.00
HRM047U2LP6	47500	208-230/3/60	16.0	7.5 x 7.5	16.53	7/8	1/2	72	1139.00
HRM047U4LP6	47500	460/3/60	7.7	7.5 x 7.5	16.53	7/8	1/2	72	1139.00
HRM054U1LP6	53700	208-230/1/60	25.0	7.5 x 7.5	17.16	7/8	1/2	87	1085.00
HRM054U2LP6	53700	208-230/3/60	17.3	7.5 x 7.5	17.16	7/8	1/2	87	1194.00
HRM054U4LP6	53700	460/3/60	8.4	7.5 x 7.5	17.16	7/8	1/2	83	1194.00
HRM058U1LP6	57800	208-230/1/60	28.8	7.5 x 7.5	17.16	7/8	1/2	87	1099.00
HRM058U2LP6	57800	208-230/3/60	17.3	7.5 x 7.5	17.16	7/8	1/2	87	1209.00
HRM058U4LP6	57800	460/3/60	9.6	7.5 x 7.5	17.16	7/8	1/2	83	1209.00
HRM060U1LP6	59700	208-230/1/60	28.8	7.5 x 7.5	17.16	7/8	1/2	87	1195.00
HRM060U2LP6	59700	208-230/3/60	17.9	7.5 x 7.5	17.16	7/8	1/2	87	1246.00
HRM060U4LP6	59700	460/3/60	9.6	7.5 x 7.5	17.16	7/8	1/2	83	1246.00

Prices above are list prices. Please call us for our discount pricing!



SM SERIES, R22

- Rotolock connections require valve or adapter if supplied solder sleeves are not used
- Capacity rated R22, 45°F evaporator, 130°F condensing



Part No.	Capacity (BTUH)	Voltage	RLA (Amps)	Quad Mount (In.)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
						Suction	Discharge		
SM090-3VI	90,049	200-230/3/60	25.0	8.6 x 8.6	20.0	1 1/8 S	3/4 S	153	2514.00
SM090-4VI	90,049	460/3/60	13.2	8.6 x 8.6	20.0	1 1/8 S	3/4 S	153	2514.00
SM110-3VI	107,830	200-230/3/60	32.1	8.6 x 8.6	22.0	1 3/8 S	7/8 S	175	3602.00
SM110-4VI	107,830	460/3/60	15.7	8.6 x 8.6	22.0	1 3/8 S	7/8 S	175	3602.00
SM115-3QAI	115,217	200-230/3/60	32.73	8.5 x 12	23.1	1 3/8 S	7/8 S	200	3240.00
SM115-3RI	115,217	200-230/3/60	32.73	8.5 x 12	23.1	1 3/4 RL x 1 1/8 S	1 1/4 RL x 3/4 S	200	3240.00
SM115-4QAI	115,217	460/3/60	14.63	8.5 x 12	23.1	1 3/8 S	7/8 S	200	3240.00
SM115-4RI	115,217	460/3/60	14.63	8.5 x 12	23.1	1 3/4 RL x 1 1/8 S	1 1/4 RL x 3/4 S	200	3240.00
SM125-3QAI	126,419	200-230/3/60	34.35	8.5 x 12	23.1	1 3/8 S	7/8 S	200	3486.00
SM125-3RI	126,419	200-230/3/60	34.35	8.5 x 12	23.1	1 3/4 RL x 1 1/8 S	1 1/4 RL x 3/4 S	200	3486.00
SM125-4QAI	126,419	460/3/60	15.95	8.5 x 12	23.1	1 3/8 S	7/8 S	200	3486.00
SM125-4RI	126,419	460/3/60	15.95	8.5 x 12	23.1	1 3/4 RL x 1 1/8 S	1 1/4 RL x 3/4 S	200	3486.00
SM160-3RI	163,000	200-230/3/60	40.85	8.5 x 12	24.9	2 1/4 RL x 1 3/8 S	1 3/4 RL x 7/8 S	225	4145.00
SM175-3QAI	174,357	200-230/3/60	47.04	11 x 12	26.7	1 5/8 S	1 1/8 S	250	4489.00
SM175-4QAI	174,357	460/3/60	22.37	11 x 12	26.7	1 5/8 S	1 1/8 S	250	4489.00
SM185-3QAI	185,475	200-230/3/60	48.73	11 x 12	26.7	1 5/8 S	1 1/8 S	250	4519.00
SM185-3RI	185,475	200-230/3/60	48.73	11 x 12	26.7	2 1/4 RL x 1 3/8 S	1 3/4 RL x 7/8 S	250	4519.00
SM185-4QAI	185,475	460/3/60	23.76	11 x 12	26.7	1 5/8 S	1 1/8 S	250	4519.00
SM185-4RI	185,475	460/3/60	23.76	11 x 12	26.7	2 1/4 RL x 1 3/8 S	1 3/4 RL x 7/8 S	250	4519.00

SZ SERIES, R407C



	Capacity (BTUH)	HP	RLA (Amps)	Voltage	Mount (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
						Suction	Discharge		
SZ084-3VI	76900	7	25.0	208-230/3/60	8.66 x 8.66	1 1/8	3/4	148	☎
SZ084-4VI	76900	7	12.1	460/3/60	8.66 x 8.66	1 1/8	3/4	148	☎
SZ090-3VI	83300	7.5	25.0	208-230/3/60	8.66 x 8.66	1 1/8	3/4	152	☎
SZ090-4VI	83300	7.5	13.2	460/3/60	8.66 x 8.66	1 1/8	3/4	152	☎
SZ100-3VI	90500	8	27.1	208-230/3/60	8.66 x 8.66	1 1/8	3/4	152	☎
SZ100-4VI	90500	8	13.6	460/3/60	8.66 x 8.66	1 1/8	3/4	152	☎
SZ110-3VI	102800	9	32.1	208-230/3/60	8.66 x 8.66	1 3/8	7/8	197	☎
SZ110-4VI	102800	9	15.7	460/3/60	8.66 x 8.66	1 3/8	7/8	197	☎
SZ115-3VI	112000	9.5	—	208-230/3/60	8.50 x 12.00	1 3/8	7/8	197	☎
SZ115-4VI	112000	9.5	—	460/3/60	8.50 x 12.00	1 3/8	7/8	197	☎
SZ120-3VI	118900	10	35.7	208-230/3/60	8.66 x 8.66	1 3/8	7/8	197	☎
SZ120-4VI	118900	10	20.7	460/3/60	8.66 x 8.66	1 3/8	7/8	197	☎
SZ125-3VI	119200	10	—	208-230/3/60	8.50 x 12.00	1 3/8	7/8	197	☎
SZ125-4VI	119200	10	—	460/3/60	8.50 x 12.00	1 3/8	7/8	197	☎
SZ160-3VI	155400	13	—	208-230/3/60	8.50 x 12.00	1 5/8	1 1/8	211	☎
SZ160-4VI	155400	13	—	460/3/60	8.50 x 12.00	1 5/8	1 1/8	211	☎
SZ161-3VI	156900	13	45.7	208-230/3/60	8.66 x 8.66	1 5/8	1 1/8	211	☎
SZ161-4VI	156900	13	22.9	460/3/60	8.66 x 8.66	1 5/8	1 1/8	211	☎
SZ175-3VI	166200	14	—	208-230/3/60	8.50 x 12.00	1 5/8	1 1/8	248	☎
SZ175-4VI	166200	14	—	460/3/60	8.50 x 12.00	1 5/8	1 1/8	248	☎
SZ185-3VI	176800	15	—	208-230/3/60	8.50 x 12.00	1 5/8	1 1/8	248	☎
SZ185-4VI	176800	15	—	460/3/60	8.50 x 12.00	1 5/8	1 1/8	248	☎
SZ240-3VI	242800	20	77.9	208-230/3/60	11.75 x 11.75	1 5/8	1 1/8	344	☎
SZ240-4VI	242800	20	35.7	460/3/60	11.75 x 11.75	1 5/8	1 1/8	344	☎
SZ300-3VI	300000	25	92.9	208-230/3/60	11.75 x 11.75	1 5/8	1 1/8	355	☎
SZ300-4VI	300000	25	49.3	460/3/60	11.75 x 11.75	1 5/8	1 1/8	355	☎
SZ380-3VI	368500	30	—	208-230/3/60	11.75 x 11.75	2 1/8	1 3/8	362	☎
SZ380-4VI	368500	30	—	460/3/60	11.75 x 11.75	2 1/8	1 3/8	362	☎

Prices above are list prices. Please call us for our discount pricing!

SCROLL COMPRESSOR



H** SERIES, R410A

Part No.	Capacity (BTUH)	HP	Voltage	RLA (Amps)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
						Suction	Discharge		
HRH031T1LP6	31000	2-1/2	208-230/1/60	17.0	16.3	3/4	1/2	68	☎
HRH031T2LP6	31000	2-1/2	208-230/3/60	12.8	16.3	3/4	1/2	68	☎
HRH032T1LP6	31998	2-1/2	208-230/1/60	16.0	16.3	3/4	1/2	68	☎
HRH032T2LP6	31998	2-1/2	208-230/3/60	12.8	16.3	3/4	1/2	68	☎
HRH036T1LP6	35407	3	208-230/1/60	21.5	16.3	3/4	1/2	68	☎
HRH036T2LP6	35407	3	208-230/3/60	14.1	16.3	3/4	1/2	68	☎
HRH038T1LP6	37940	3	208-230/1/60	21.0	16.3	3/4	1/2	71	☎
HRH038T2LP6	37940	3	208-230/3/60	14.7	16.3	3/4	1/2	71	☎
HRH040T1LP6	41539	3-1/4	208-230/1/60	21.0	17.3	7/8	1/2	71	☎
HRH040T2LP6	41539	3-1/4	208-230/3/60	16.0	17.3	7/8	1/2	71	☎
HRH041T1LP6	41310	3-1/4	208-230/1/60	22.4	17.9	7/8	1/2	82	☎
HRH041T2LP6	41310	3-1/4	208-230/3/60	16.0	17.9	7/8	1/2	82	☎
HRH044T1LP6	44408	3-3/4	208-230/1/60	24.3	17.9	7/8	1/2	82	☎
HRH044T2LP6	44408	3-3/4	208-230/3/60	16.7	17.9	7/8	1/2	82	☎
HRH049T1LP6	49023	4	208-230/1/60	25.0	17.9	7/8	1/2	82	☎
HRH049T2LP6	49023	4	208-230/3/60	16.7	17.9	7/8	1/2	82	☎
HRH051T1LP6	51835	4	208-230/1/60	26.3	17.9	7/8	1/2	82	☎
HRH051T2LP6	51835	4	208-230/3/60	17.6	17.9	7/8	1/2	82	☎
HRH054T1LP6	54528	4-1/2	208-230/1/60	29.0	17.9	7/8	1/2	82	☎
HRH054T2LP6	54528	4-1/2	208-230/3/60	17.3	17.9	7/8	1/2	82	☎
HRH056T1LP6	56924	4-3/4	208-230/1/60	30.1	17.9	7/8	1/2	82	☎
HRH056T2LP6	56924	4-3/4	208-230/3/60	17.3	17.9	7/8	1/2	82	☎
HLH068T2LC6	67435	6	208-230/3/60	23.0	17.9	7/8	1/2	82	☎
HLH068T4LC6	67435	6	460/3/60	12.2	17.9	7/8	1/2	82	☎
HLJ072T2LC6	72532	6-1/2	208-230/3/60	22.4	17.9	7/8	1/2	82	☎
HLJ072T4LC6	72532	6-1/2	460/3/60	12.2	17.9	7/8	1/2	82	☎
HLJ083T2LC6	83127	7	208-230/3/60	26.0	17.9	7/8	1/2	82	☎
HLJ083T4LC6	83127	7	460/3/60	13.0	17.9	7/8	1/2	82	☎

H* SERIES, R407C R22

Part No.	Capacity (BTUH)	HP	Voltage	RLA (Amps)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
						Suction	Discharge		
HRP038T1LP6	35500	3	208-230/1/60	—	16.3	3/4	1/2	68	☎
HRP038T2LP6	35500	3	208-230/3/60	12.2	16.3	3/4	1/2	68	☎
HRP040T1LP6	36500	3-1/4	208-230/1/60	—	16.3	3/4	1/2	68	☎
HRP040T2LP6	36500	3-1/4	208-230/3/60	12.8	16.3	3/4	1/2	68	☎
HRP042T1LP6	38500	3-1/2	208-230/1/60	—	16.3	3/4	1/2	68	☎
HRP042T2LP6	38500	3-1/2	208-230/3/60	14.1	16.3	3/4	1/2	68	☎
HRP045T1LP6	43500	3-3/4	208-230/1/60	—	17.3	7/8	1/2	68	☎
HRP045T2LP6	43500	3-3/4	208-230/3/60	16	17.3	7/8	1/2	68	☎
HRP047T1LP6	45100	4	208-230/1/60	—	17.3	7/8	1/2	68	☎
HRP047T2LP6	45100	4	208-230/3/60	16	17.3	7/8	1/2	68	☎
HRP048T1LP6	44800	4	208-230/1/60	—	17.9	7/8	1/2	82	☎
HRP048T2LP6	44800	4	208-230/3/60	—	17.9	7/8	1/2	82	☎
HRP051T1LP6	49000	4-1/4	208-230/1/60	25.6	17.9	7/8	1/2	82	☎
HRP051T2LP6	49000	4-1/4	208-230/3/60	16.7	17.9	7/8	1/2	82	☎
HRP054T1LP6	50900	4-1/2	208-230/1/60	—	17.9	7/8	1/2	82	☎
HRP054T2LP6	50900	4-1/2	208-230/3/60	—	17.9	7/8	1/2	82	☎
HRP058T1LP6	54500	4-3/4	208-230/1/60	—	17.9	7/8	1/2	82	☎

Prices above are list prices. Please call us for our discount pricing!

Continued on next page

**H* SERIES, R407C R22 (Cont'd)**

Part No.	Capacity		Voltage	RLA (Amps)	Height (In.)	Connections (In.)		Ship Wgt. (Lbs.)	Price
	(BTUH)	HP				Suction	Discharge		
HRP058T2LP6	54500	4-3/4	208-230/3/60	—	17.9	7/8	1/2	82	☎
HRP060T1LP6	56100	5	208-230/1/60	—	17.9	7/8	1/2	82	☎
HRP060T2LP6	56100	5	208-230/3/60	16.7	17.9	7/8	1/2	82	☎
HLP068T2LC6	63500	5-1/2	208-230/3/60	—	17.9	7/8	1/2	82	☎
HLP068T4LC6	63500	5-1/2	460/3/60	—	17.9	7/8	1/2	82	☎
HLP072T2LC6	68100	6	208-230/3/60	—	17.9	7/8	1/2	82	☎
HLP072T4LC6	68100	6	460/3/60	9.6	17.9	7/8	1/2	82	☎
HLP075T2LC6	73000	6-1/2	208-230/3/60	—	17.9	7/8	1/2	82	☎
HLP075T4LC6	73000	6-1/2	460/3/60	10.3	17.9	7/8	1/2	82	☎
HLP081T2LC6	75300	7	208-230/3/60	21.1	17.9	7/8	3/4	82	☎
HLP081T4LC6	75300	7	460/3/60	11	17.9	7/8	3/4	82	☎
HCP094T2LC6	87500	7-1/2	208-230/3/60	25.6	21.1	1 1/8	7/8	97	☎
HCP094T4LC6	87500	7-1/2	460/3/60	13.5	21.1	1 1/8	7/8	97	☎
HCP109T2LC6	101500	9	208-230/3/60	—	21.5	1 1/8	7/8	100	☎
HCP109T4LC6	101500	9	460/3/60	16	21.5	1 1/8	7/8	100	☎
HCP120T2LC6	110800	10	208-230/3/60	35.3	21.5	1 1/8	7/8	100	☎
HCP120T4LC6	110800	10	460/3/60	19.2	21.5	1 1/8	7/8	100	☎

Prices above are list prices. Please call us for our discount pricing!